

DECLARATION OF PERFORMANCE

No.: 110040

1. **Product:**
PEGOLAND BLANCO
2. **Manufacturer:**
GRUPO PUMA ESPAÑA located at:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
PEGOLAND BLANCO, normal-setting cementitious adhesive for the installation of internal floor and wall coverings. Suitable for laying medium to high absorption level ceramic tiles. Unsuitable for exterior areas.
4. **Evaluation system:**
3
5. **Notified bodies:**
The following type tests were carried out: Nos. 71352, 71355, 71364, 71375, 71387, 71392, 71412, 71421, 71427, 71442, 71474, 71476,
71484 and 75258, dated February, March and April 2004, at CEMOSA No. 1377 (Málaga); and test No. 4009483, dated May 2004, No. 09/1081-3153, dated January 2010, and No. 31213991, dated November 2006, at APPLUS No. 0370 (Barcelona), obtaining the same product performance results for all manufacturing plants.
6. **Declared performances:**

Essential characteristics	Performances	Harmonized Technical Specification
Reaction to fire:	A1fl and A1 Class	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after thermal ageing - Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$ NPD NPD	
Hazardous substances:	See safety data sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on behalf of the manufacturer:

Place and date of issue: Málaga, 02/01/2025



Technical Director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 04	
PEGOLAND BLANCO Nº: 110040 EN-12004:2007+A1:2012 Normal setting, cementitious adhesive for the installation of interior walls and floors. Suitable for laying medium to high absorption level ceramic tiles. Unsuitable for exterior areas.	
Reaction to fire:	A1fl and A1 Class
Adhesion: - Initial tensile adhesion strength:	≥ 0,5 N/mm ²
Durability: - Tensile adhesion strength after water immersion:	≥ 0,5 N/mm ²
Hazardous substances: See safety data sheet	