

DECLARATION DE PERFORMANCES

Nº: 150087

1. **Product:**
TRADITERM NC
2. **Manufacturer:**
GRUPO PUMA SL, located in:
Avda Agrupación Córdoba 17,
14014 Córdoba
www.grupopuma.com
3. **Intended use:** Mortar for GP current use, which is used as an adhesive in conventional and unconventional supports of insulating plates of expanded polystyrene, EPS of graphite and mineral wool, for thermal insulation systems by the exterior, ETICS, both in new construction and rehabilitation.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type A1	EN-998-1:2010
Water absorption	W0	
Diffusion coefficient of water vapour	$\mu \leq 20$	
Thermal conductivity : ($\lambda_{10, dry}$)	0.4 W/mK	
Adhesion	≥ 1.0 N/mm ² Shape breakage B	
Durability	NPD	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5.
This declaration of features is issued under the sole responsibility of manufacturer stated in point 2.
Signed by and on manufacturer behalf
Place and date of issue: Córdoba, 25/08/2020



Technical director: José A. Ferre Martínez



GRUPO PUMA S.L
Avda. Agrupación Córdoba 17
14014 Córdoba
20

TRADITERM NC
Nº: 150087
EN-998-1

Mortar for GP current use, which is used as an adhesive in conventional and unconventional supports of insulating plates of expanded polystyrene, EPS of graphite and mineral wool, for thermal insulation systems by the exterior, ETICS, both in new construction and rehabilitation.

Reaction to fire	Type A1
Water absorption	W0
Diffusion coefficient of water vapour	$\mu \leq 20$
Thermal conductivity : ($\lambda_{10,dry}$)	0.4 W/mK
Adhesion	≥ 1 N/mm ² Shape breakage B