

## DECLARATION DE PERFORMANCES

### Nº: 200123-01

1. **Product:**  
MORCEM BLOQUE
2. **Manufacturer:**  
GRUPO PUMA SL located in:  
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17  
14014 CÓRDOBA  
[www.grupopuma.com](http://www.grupopuma.com)
3. **Intended use:**  
Mortar prescribed for masonry for common use (G), for erecting works of masonry, exposed brick and block of concrete.
4. **Evaluation system:**  
4
5. **Declared performances :**

Essentials characteristics	Performance	Harmonised technical specification
Proportion of components (by volume)	Cement 25% Aggregates 75%	EN 998-2:2018
Bonding strength	NPD	
Content in chloride ions	NPD	
Reaction to fire	Type A1	
Water absorption	$\leq 0,2 \text{ kg/m}^2 \cdot \text{min} 0,5$	
Diffusion coefficient of water vapour	$\mu \leq 15/35$	
Thermal conductivity ( $\lambda_{10, \text{dry}}$ )	NPD	
Durability	NPD	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5. This declaration of features is issued under the sole responsibility of manufacturer stated in point 2, in accordance with Regulation (EU) No 305/2011.

Signed by and on manufacturer behalf

Place and date of issue:

Córdoba, 06/02/2023



Technical director: Jose A. Ferre Martínez



GRUPO PUMA ESPAÑA, S.L.  
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17  
14014 CÓRDOBA  
18

**MORCEM BLOQUE**

**Nº: 200123-01**

**EN 998-2**

Mortar prescribed for masonry for common use (G), for erecting works of masonry, exposed brick and block of concrete.

**Proportion of components (by volume):**

Cement 25%

Aggregates 75%

**Reaction to fire :** Type A1

**Water absorption:**  $\leq 0,2 \text{ kg/m}^2 \cdot \text{min} 0,5$

**Diffusion coefficient of water vapour:**  $\mu \leq 15/35$

**Hazardous substances:** See safety datasheet