

DECLARATION OF PERFORMANCES

Nº : 120025-131

1. **Product:**
PEGOLAND ESPECIAL BLANCO
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Normal setting cementitious adhesive, with reduced slip and extended open time, Pegoland Especial Blanco, for bonding pieces with absorption >3% and glass mosaics, on interior walls and floors, and exterior floors. Suitable for the installation of low absorption ($\leq 3\%$) tiles in interior residential and public pedestrian floors and walls, if the length of the longer side of the tile is ≤ 30 cm.
4. **Evaluation system:**
3
5. **Notified bodies:**
Type tests were conducted under report number 001-24/013054/1, dated April 2024; report numbers 001-24/019432/1, 001-24/019476/1, 001-24/019617/1, 001-24/019943/1, 001-24/019808/1 and 001-24/019627/1, dated May 2024; report number 001-24/024276/1, dated June 2024; and report numbers 001-24/030891/1, 001-24/030654/1, 001-24/030900/1, 001-24/029547/1, 001-24/029644/1, 001-24/030340/1 and 001-24/030167/1 dated July 2024, at CEMOSA (No. 1377, Málaga), obtaining identical product performance results for all manufacturing plants.
6. **Declared performances:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after heat ageing - Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performance of the product identified in point 1 conforms with the declared performance in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on manufacturer's behalf:
Place and date of issue: Málaga, 07/01/2025



Technical Director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 24	
PEGOLAND ESPECIAL BLANCO Nº: 120025-131 EN-12004:2007+A1:2012 Normal setting cementitious adhesive, with reduced slip and extended open time. Suitable for interior walls and floors and for exterior floors.	
Reaction to fire:	E Class
Adhesion:	
- Initial tensile adhesion strength	≥ 0,5N/mm ²
Durability:	
- Tensile adhesion strength after water immersion:	≥ 0,5 N/mm ²
- Tensile adhesion strength after heat ageing:	≥ 0,5 N/mm ²
- Tensile adhesion strength after freeze-thaw cycles:	≥ 0,5 N/mm ²
Hazardous substances:	See safety datasheet