

DECLARATION OF PERFORMANCES

Nº: 100195-392

1.- Product: TRADITERM CERAMIC

2.-Manufacturer: GRUPO PUMA SL with registered address at: Avda. Agrupación Córdoba 17,14014 Córdoba www.grupopuma.com

3.-Intended use: Two components cement based improved adhesive, highly deformable, non slip and extended open time for the tiling application in System Traditerm Ceramic (ETICS) with DIT PLUS nº605/14.

4.-Evaluation System: 3

5.- Notified bodies: Tests type 76709 have been carried out dated April 1, 2004 in CEMOSA No. 1377 (Málaga)

6.-Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN-12004:2007 +A1:2012
Adherence: Initial tensile adhesion strength	$\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6. This declaration of features is issued under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf:

Place and date of issue: Málaga, 28/05/2019



Technical Director: Jose A. Ferre Martínez



GRUPO PUMA SL
Avda Agrupación Córdoba 17
14014 Córdoba
04
Nº: 100195-392

EN 12004: 2007+A1:2012

TRADITERM CERAMIC

Two components cement based improved adhesive, highly deformable, non slip and extended open time for the tiling application in System Traditerm Ceramic (ETICS) with DIT PLUS nº605/14.

- **Reaction to fire:** Class E
- **Adherence:**
 - Initial tensile adhesion strength:** $\geq 1\text{N/mm}^2$
- **Durability:**
 - **Tensile adhesion after water immersion:** $\geq 1\text{N/mm}^2$
 - **Tensile adhesion after heat aging:** $\geq 1\text{N/mm}^2$
 - **Tensile adhesion after freeze/thaw cycles:** $\geq 1\text{N/mm}^2$
- **Hazardous substances:** See safety datasheet