

DECLARATION OF BENEFITS

Nº: 840251

1. **Product:**
TRADITERM TACO DE ANCLAJE
2. **Manufacturer:**
GRUPO PUMA SLresiding at :
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Mechanical tapping dowel with polyamide nail and short embedding depth for fixing the insulation materials.
4. **Evaluation system:**2+
5. **Notified Body:**

European Evaluation Documentation	ETAG 014, edition February 2011
	European Technical Assessment - ETA-23/0495 of 13.07.2023
	Deutsches Institut für Bautechnik - DIBt
	Identification of the notified body - 1488

6. **Declared benefits:**

Essential characteristic	Performance										
	Base material	Concrete C12/15	Concrete C20/25 - C50/60	Clay bricks MZ	Calcium silicate bricks KS	Calcium silicate hollow block KSL	Vertically perforated clay bricks HLZ	Vertically perforated clay bricks porotherm 25	Lightweight concrete blocks LAC	Autoclaved concrete blocks AAC2	Autoclaved concrete blocks AAC7
Characteristic tension resistance	Nrk[kN]	0,5	0,75	0,75	0,6	0,6	0,6	0,4	0,6	0,5	0,6
Edge distances and spacing	Min. allowable spacing = 100mm					Min. allowable edge distance = 100mm					
Displacement	N[kN]/δ[mm]	0,17/1,4	0,25/1,8	0,25/0,6	0,2/1,1	0,2/1,5	0,2/1,4	0,13/0,5	0,2/1,5	0,17/1,3	0,2/1,8
Plate stiffness	[kN/mm]	0,5									
Point thermal transmittance	[W/k]	0,001* / 0,000**									

*) surface mount; **) immersed mount

The performance of the product identified in item 1 is in conformity with the performance declared in item 6. This declaration of performance is issued under the sole responsibility of the distributor identified in point 2.

Signed by and on behalf of the distributor:
Place and Date of issue: Cordoba, 01/08/23

A handwritten signature in purple ink, consisting of a stylized, cursive script that appears to be the initials "JAF" followed by a long horizontal line extending to the right.

Technical Director: Jose A. Ferre Martínez