

DECLARATION OF PERFORMANCE

Nº.: 100055


1. **Product:**
PEGOLAND GEL PORCELANICO C2TE GRIS
2. **Manufacturer:**
GRUPO PUMA SL located at:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Improved cementitious adhesive with reduced slip and extended open time, Pegoland Gel Porcelánico C2TE gris, for the installation of interior and exterior floors, interior walls and exterior plinths, swimming pools tiling, underfloor heating, overlays in indoor flooring, adhesion of all type of ceramic tiles, porcelain tiles, marble, granite, and other natural stones.
4. **Evaluation system:**
3
5. **Notified bodies:**
The following type tests were carried out: Nos. 001-22/005960/1, 001-22/005946/1 and 001-22/005958/1 dated February 2022; No. 001-22/009081/1 dated April 2022; and No. 001-22/036945/1 dated November 2022, at CEMOSA No. 1377 (Málaga), obtaining the same product performance results for all manufacturing plants.
6. **Declared performances:**

Essential characteristics	Performances	Harmonized Technical Specification
Reaction to fire:	E Class	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion	$\geq 1 \text{ N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after heat ageing - Tensile adhesion strength after freeze- thaw cycles	$\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$	
Hazardous substances:	See safety data sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on behalf of the manufacturer:

Place and date of issue: Málaga, 03/01/2025



Technical Director: Jose A. Ferre Martínez



1377

GRUPO PUMA SL
Avda. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba)
22

PEGOLAND GEL PORCELANICO C2TE GRIS

Nº: 100055

IN 12004:2007+A1:2012

Improved cementitious adhesive with reduced slip and extended open time, suitable for interior and exterior floors and exterior plinths.

Reaction to fire: E Class

Adhesion:
- Initial adhesion to traction: $\geq 1 \text{ N/mm}^2$

Durability:
- Tensile adhesion strength after water immersion: $\geq 1 \text{ N/mm}^2$
- Tensile adhesion strength after heat ageing: $\geq 1 \text{ N/mm}^2$
- Tensile adhesion strength after freeze–thaw cycles: $\geq 1 \text{ N/mm}^2$

Hazardous substances: See safety data sheet