

## DECLARATION OF PERFORMANCE


### No.: 860006

1. **Product:**  
MORCEMCAL BASE
2. **Manufacturer:**  
GRUPO GRUPO PUMA ESPAÑA located at:  
AVDA. AGRUPACIÓN CÓRDOBA, Núm. 17  
14014 CÓRDOBA  
[www.grupopuma.com](http://www.grupopuma.com)
3. **Intended use:**  
CR CSII W1 coloured rendering and plastering mortar, based on natural hydraulic lime, for external and internal rendering and plastering, with thicknesses ranging from 0.5 to 1.5 cm.
4. **Evaluation system:**  
4
5. **Declared performances:**

| Essential characteristics                           | Performances                                      | Harmonized Technical Specification |
|-----------------------------------------------------|---------------------------------------------------|------------------------------------|
| Reaction to fire                                    | A1 Type                                           | EN 998-1:2018                      |
| Water absorption                                    | W1                                                |                                    |
| Water vapour permeability coefficient               | $\mu \leq 6$                                      |                                    |
| Thermal Conductivity ( $\lambda_{10 \text{ dry}}$ ) | NPD                                               |                                    |
| Adhesion                                            | $\geq 0,3 \text{ N/mm}^2$ Type<br>of failure: A/B |                                    |
| Durability:                                         | NPD                                               |                                    |
| Hazardous substances                                | Consult safety data sheet                         |                                    |

The performance of the product identified in point 1 conforms with the declared performance in point 5.  
This Declaration of Performance is issued under the sole responsibility of the manufacturer indicated in point 2 in accordance with Regulation (EU) No 305/2011.

Signed by and on behalf of the manufacturer:  
Place and date of issue: Córdoba, 07/05/25.



Technical Director: Jose A. Ferre Martínez

|                                                                                                                                                                                                                                                                             |                                                |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| CE                                                                                                                                                                                                                                                                          |                                                |
| <p>GRUPO PUMA ESPAÑA S.L<br/>         AVDA. AGRUPACIÓN CÓRDOBA, Núm. 17<br/>         14014 CÓRDOBA</p> <p>25</p>                                                                                                                                                            |                                                |
| <p><b>MORCEMCAL BASE</b></p> <p><b>No.: 860006</b></p> <p><b>EN 998-1</b></p> <p>CR CSII W1 coloured rendering and plastering mortar, based on natural hydraulic lime, for external and internal rendering and plastering, with thicknesses ranging from 0.5 to 1.5 cm.</p> |                                                |
| <p><b>Reaction to fire Class</b><br/>A1</p>                                                                                                                                                                                                                                 |                                                |
| <b>Water absorption</b>                                                                                                                                                                                                                                                     | W1                                             |
| Water vapour permeability coefficient                                                                                                                                                                                                                                       | $\mu \leq 6$                                   |
| Adhesion                                                                                                                                                                                                                                                                    | $\geq 0,3 \text{ N/mm}^2$ Type of failure: A/B |