

DECLARATION DE PERFORMANCES Nº: 150078

1. **Product:**
TRADITERM FLEXIBLE
2. **Manufacturer:**
GRUPO PUMA SL, located in:
Avda Agrupación Córdoba 17,
14014 Córdoba
www.grupopuma.com
3. **Intended use:** Mortar with maximum flexibility, for the coating of insulating panels in the thermal insulation system exterior TRADITERM FLEXIBLE.
4. **Evaluation system:**
3
5. **Notified bodies:**
LGAI Technological Center S.A.
Test report Nº. 22/32305399-S
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Water vapour permeability	Medium (V2)	EN-15824:2017
Water absorption	Medium (W2)	
Adhesion	>0.3 MPa	
Durability	PND	
Thermal conductivity	0,69-0,89 W/mK	
Reaction to fire	B-s2, d0	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.
This declaration of features is issued under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf
Place and date of issue: Córdoba, 14/10/2022



Technical director: José A. Ferre Martínez



22/32305399-S

GRUPO PUMA S.L
Avda. Agrupación Córdoba 17
14014 Córdoba
17

TRADITERM FLEXIBLE
Nº: 150078
EN-15824:2017

Mortar with maximum flexibility, for the coating of insulating panels in the thermal insulation system exterior TRADITERM FLEXIBLE.

Water vapour permeability	Medium (V2)
Water absorption	Medium (W2)
Adhesion	>0.3 MPa
Durability	PND
Thermal conductivity	0,69-0,89 W/mK
Reaction to fire	B-s2, d0
Hazardous substances	See safety datasheet