

DECLARATION OF PERFORMANCE


Nº.: 100050-434

1. **Product:**
PEGOLAND GEL PORCELANICO C2TE BLANCO
2. **Manufacturer:**
GRUPO PUMA SL located at:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Improved cementitious adhesive with reduced slip and extended open time, Pegoland Gel Porcelánico C2TE Blanco, for the installation of interior and exterior floors, interior walls and plinths, swimming pool tiling, underfloor heating, overlays in indoor flooring, adhesion of all type of ceramic tiles, porcelain tiles, marble, granite, and other natural stones.
4. **Evaluation system:**
3
5. **Notified bodies:**
The following type tests were carried out: No. 01-18/032172/1 dated October 2018; No. 01-19/043045/1 dated November 2019; No. 01-21/001079/1 dated January 2021; Nos. 01-21/006896/1, 01-21/005758/1, 01-21/006034/1, 01-21/006865/1 and 01-21/006032/1 dated March 2021; and No. 001-23/035498/1 dated September 2023, at CEMOSA No. 1377 (Málaga), obtaining the same product performance results for all manufacturing plants.
6. **Declared performances:**

Essential characteristics	Performances	Harmonized Technical Specification
Reaction to fire:	Class E	EN-12004:2008+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1 \text{ N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after heat ageing - Tensile adhesion strength after freeze - thaw cycles	$\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$	
Hazardous substances:	See safety data sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on behalf of the manufacturer:
Place and date of issue: Málaga, 03/01/2025



Technical Director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 19	
PEGOLAND GEL PORCELANICO C2TE BLANCO N.º: 100050-434 EN-12004:2008+A1:2012 Improved cementitious adhesive with reduced slip and extended open time, suitable for interior and exterior plinths and floors.	
Reaction to fire:	E Class
Adhesion: - Initial tensile adhesion strength:	$\geq 1 \text{ N/mm}^2$
Durability: - Tensile adhesion strength after water immersion: - Tensile adhesion strength after heat ageing: - Tensile adhesion strength after freeze-thaw cycles:	$\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$
Hazardous substances:	See safety data sheet