

DECLARATION OF PERFORMANCES

Nº: 230038

1.- Product: MORCEMDRY SF

2.-Intended use: One-component, semi-flexible surface protection coating mortar with a minimum layer thickness of 2 mm.

3.-Manufacturer: GRUPO PUMA SL with: Avda. Agrupación Córdoba 17 , 14014 Córdoba (Málaga).www.grupopuma.com

4.-Evaluation system: 4

5.-Declared performances:

Essential characteristics	Performances	Harmonised Standards
Penetration rate	Class I < 10 mm	EN-1504-2:2004
Capillary absorption and water permeability	$W \leq 0.1 \text{ kg/m}^2 \text{ h}^{0.5}$	
Thermal compatibility	Comply	
Adhesive strength by tensile test	Comply	
Hazardous substances	See Safety Data Sheet	

Product performances identified in point 1 are in accordance to performances stated in point 5
This performance statement is issued under sole manufacturer responsibility indicated in point 3.

Signed by and on manufacturer behalf:

Place and date of issue: Málaga, 26/04/2021



Technical director: Jose A. Ferre Martínez



GRUPO PUMA SL
Avda. Agrupación Córdoba 17, 14014 Córdoba
21
Nº: 230038

EN-1504-2

MORCEMDRY SF

One-component, semi-flexible surface protection coating mortar with a minimum layer thickness of 2 mm.

Capillary absorption and water permeability: $\leq 0.1 \text{kg/m}^2 \text{h}^{0.5}$

Penetration rate: Class I

Thermal compatibility: Comply

Adhesive strength by tensile test: Comply