

**DECLARATION OF PERFORMANCES**  
**Nº: 105293**


- 1. Product:**  
PEGOLAND PROFESIONAL PORCELANICO
- 2. Manufacturer:**  
GRUPO PUMA SL located in:  
Avda. Agrupación Córdoba, 17  
14014 Córdoba (Córdoba)  
www.grupopuma.com
- 3. Intended use:**  
Improved cementitious adhesive with reduced slip and extended open time, Pegoland Profesional Porcelanico. For the installation of interior and exterior floorings, interior coverings and baseboards, swimming pool coverings and, radiant heating and overlaps in interior floorings, adhesion of all types of ceramic pieces, porcelain stoneware, marble, granite and natural stone.
- 4. Evaluation system:**  
3
- 5. Notified bodies:**  
They have carried out the type tests nº 01-18/032172/1, 01-18/032170/1, 01-18/032176/1 and 01-18/032173/1 dated October, November and December 2018, at CEMOSA nº 1377 (Málaga) obtaining the same results of the product for all factories.
- 6. Declared performances:**

Essential characteristics	Performances	Harmonized technical specifications
<b>Reaction to fire</b>	Class E	EN-12004:2007+A1:2012
<b>Adhesion</b> - Initial tensile adhesion	$\geq 1\text{N/mm}^2$	
<b>Durability</b> - Tensile adhesion after immersion in water. - Tensile adhesion after thermal aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
<b>Hazardous substances</b>	See safety data sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.  
This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.  
Signed by and on behalf of the manufacturer:  
Place and Date of issue: Málaga, 08/01/2019



Technical director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 21	
<b>PEGOLAND PROFESIONAL PORCELANICO</b>  <b>Nº: 105293</b>  <b>EN-12004:2007+A1:2012</b>  Improved deformable cementitious adhesive with reduced slip and extended open time, for interior and exterior floorings and coverings.	
<b>Reaction to fire:</b>	Class E
<b>Adhesion</b>	
- Initial tensile adhesio	$\geq 1\text{N/mm}^2$
<b>Durability</b>	
- Tensile adhesion after immersion in water.	$\geq 1\text{N/mm}^2$
- Tensile adhesion after thermal aging	$\geq 1\text{N/mm}^2$
- Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$
<b>Hazardous substances</b>	See safety data sheet