

DECLARATION OF PERFORMANCES

Nº: 340001

1. **Product:**
PEGOLAND ELASTIC (R2T)
2. **Manufacturer:**
GRUPO PUMA SL based in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba).
www.grupopuma.com
3. **Intended use:**
Improved reactive adhesive for ceramic tiles (R2), for interior and exterior ceramic tiles on floors and walls.
4. **Evaluation system:**
3
5. **Notified Agencies:**
Notified body Modena Centro Prove S.r.l. Modena - Italy - N°1599, has determined the shear adhesion forces in a sample at the manufacturer's headquarters, according to system 3, and has delivered test relation No. 20188770/1
6. **Declared performances:**


Essential characteristics	Performances	Harmonized standards
Reaction to fire :	Class E	EN-12004:2007 + A1:2012
Initial shear strength	$\geq 2 \text{ N/mm}^2$	
Shear resistance after immersion in water	$\geq 2 \text{ N/mm}^2$	
Shear resistance after thermal shocks	$\geq 2 \text{ N/mm}^2$	
Hazardous substances	See safety datasheet	

The performances of the product define in point 1 comply with the performances declared in point 6.
This declaration of features is issued under the sole responsibility of manufacturer stated in point 3
Signed by and on manufacturer behalf:



Place and date of issue: Málaga, 24/06/2019

Technical director: Jose A. Ferre Martínez

 1599	
GRUPO PUMA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 19	
PEGOLAND ELASTIC Nº: 340001 EN 12004: 2007 + A1:2012 Improved reactive adhesive for ceramic tiles (R2), for interior and exterior ceramic tiles on floors and walls.	
Reaction to fire:	Class E
Performances:	
- Initial shear strength:	$\geq 2\text{N/mm}^2$
- Shear resistance after immersion in water:	$\geq 2\text{N/mm}^2$
- Shear resistance after thermal shocks:	$\geq 2\text{N/mm}^2$
Hazardous substances:	See safety datasheet