

## DECLARATION OF PERFORMANCES

### Nº: 105285

- 1. Product:**  
PEGOLAND PROFESIONAL ELITE BLANCO
- 2. Manufacturer:**  
GRUPO PUMA SL located in:  
Avda. Agrupación Córdoba, 17  
14014 Córdoba (Córdoba)  
www.grupopuma.com
- 3. Intended use:**  
Highly deformable improved cementitious adhesive with reduced slip and extended open time, PEGOLAND PROFESIONAL ELITE BLANCO, for gluing interior and exterior floor and wall coverings. Special for facades, large surface pavements, radiant heating floors, overlays, cold rooms, swimming pools and cementitious waterproofing.
- 4. Evaluation system:**  
3
- 5. Notified bodies:**  
Type tests nº 001-21/037268/1 and nº 001-21/037280/1 of November 2021 have been carried out at CEMOSA nº 1377 (Málaga).
- 6. Declared performances:**

Essential characteristics	Performances	Harmonized technical specifications
<b>Reaction to fire</b>	Class E	EN-12004:2008+A1:2012
<b>Adhesion</b> - Initial tensile adhesion	$\geq 1\text{N/mm}^2$	
<b>Durability</b> - Tensile adhesion after immersion in water. - Tensile adhesion after thermal aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
<b>Hazardous substances</b>	See safety data sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.

Signed by and on behalf of the manufacturer:  
Place and Date of issue: Málaga, 17/11/2021



Technical director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 21	
<b>PEGOLAND PROFESIONAL ELITE BLANCO</b>  <b>Nº: 105285</b>  <b>EN-12004:2008+A1:2012</b>  Highly deformable improved cementitious adhesive with reduced slip and extended open time, for floor and wall coverings, interior and exterior. Special for facades, large surface pavements, radiant heating floors, overlays, cold rooms, swimming pools and cementitious waterproofing.	
<b>Reaction to fire:</b>	Class E
<b>Adhesion</b>	
- Initial tensile adhesion	≥ 1N/mm <sup>2</sup>
<b>Durability</b>	
- Tensile adhesion after immersion in water.	≥ 1N/mm <sup>2</sup>
- Tensile adhesion after thermal aging	≥ 1N/mm <sup>2</sup>
- Tensile adhesion after freeze/thaw cycles	≥ 1N/mm <sup>2</sup>
-	
<b>Hazardous substances</b>	See safety data sheet