(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



Version 1

Revision date: 30/01/2025

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier. Product Name:

PUMAPLAST EXTERIOR CERÁMICA

1.2 Relevant identified uses of the substance or mixture and uses advised against. Exterior repair putty

Uses advised against: Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

GRUPO PUMA ESPAÑA S.L. AVDA. AGRUPACIÓN CÓRDOBA, NUM. 17 14014 CÓRDOBA - CÓRDOBA - ESPAÑA Tfno.: +34 957 102 210 - Fax: +34 957 44 19 92 fds@grupopuma.com http://www.grupopuma.com

1.4 Emergency telephone number:

+34 957 102 210 ((8:30-13:30 / 16:00-19:00 h.) (working hours))

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008: Eye Dam. 1 : Causes serious eye damage. STOT SE 3 : May cause respiratory irritation. Skin Sens. 1 : May cause an allergic skin reaction. Skin Irrit. 2 : Causes skin irritation.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008: Pictograms:



Signal Word:

Danger

- Hazard statements:
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H335 May cause respiratory irritation.

Precautionary statements:

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.

(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



Version 1

Revision date: 30/01/2025

P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/
P310	Immediately call a POISON CENTER/doctor/
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/national/international regulation.

Contains:

Cement, portland, chemicals

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name Concentr		Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 65997-15-1 EC No: 266-043-4	[2] Cement, portland, chemicals	>= 25% < 50 %	Eye Dam. 1, H318 - STOT SE 3, H335 - Skin Irrit. 2, H315 - Skin Sens. 1B, H317	-
CAS No: 13397-24-5	[2] Calcium sulfate hydrate	< 0,1%	-	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[2] Substance with a national workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eve contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



Revision date: 30/01/2025

Skin contact.

Version 1

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Repeated or prolonged eye contact may cause stinging, tearing, redness, swelling, and blurred vision.

Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

Request immediate medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



Version 1

Revision date: 30/01/2025

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
		España [1]	Eight hours		4 (fracción respirable)
			Short term		
		Italia [2]	Eight hours		10
		Italia [2]	Short term		4 (fracción respirable) 10 1 (O valor aplica-se a partículas sem amianto e contendo menos de 1% de sílica cristalina, Fração respirável) 1 (Respirable particulate matter) 10 (Total dust) 5 (Respirable fraction) 15 (Total dust) 5 (Respirable fraction) 50 (mppcf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Conversion factors -
		Portugal [3] (n/a)	Eight hours		partículas sem amianto e contendo menos de 1% de sílica cristalina,
			Short term		1 (Respirable
		United States	Eight hours		
			Short term		
Cement, portland, chemicals	65997-15-1	United States [4] (Cal/OSHA)	Eight hours		
			Short term		partículas sem amianto e contendo menos de 1% de sílica cristalina, Fração respirável) 1 (Respirable particulate matter) 10 (Total dust) 5 (Respirable fraction) "10 (Total dust) 5 (Respirable fraction) 50 (mppcf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Conversion factors -
		United States	Eight hours		"10 (Total dust)
		[5] (NIOSH)	Short term		
		United States [6] (OSHA)	Eight hours		(Respirable fraction) 50 (mppcf:Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques.
			Short term		

(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



Version 1

Revision date: 30/01/2025

		España [1]	Eight hours	10
			Short term	
		Portugal [3]	Eight hours	10 (Fração inalável)
		(n/a)	Short term	
		-24-5 United States	Eight hours	10 (Inhalable
Calcium sulfate hydrate	13397-24-5			particulate matter)
			Short term	
		United States	Eight hours	"10 (Total dust)
		[5] (NIOSH)	Short term	
		United States	Eight hours	"10 (Total dust)
		[6] (OSHA)	Short term	

[1] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad y Salud en el Trabajo (INSST) para el año 2024.

[2] Secondo il Decreto Legislativo del Governo n.277, 15/08/1991, il Decreto Legislativo n.66 ed il Decreto Ministeriale 26/02/2004.

[3] De acordo com a Norma Portuguesa 1796 adotou pelo Instituto português de qualidade.

[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health,

Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100. [6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %			
Uses:	Exterior repair putty			
Breathing protect	tion:			
PPE:	Particle filter mask			
Characteristics:	«CE» marking, category III. Made of filtering material, it covers nose, mouth and chin.			
CEN standards:	EN 149			
Maintenance:	Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment, it should be replaced after use.			
Observations:	Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.			
Filter Type needed	: P2			
Hand protection				
PPE:	Non-disposable protective gloves against chemicals.			
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.			
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420			
Maintenance: Observations:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material. They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could			
Material:	reduce their strength. DVC (reducing charge) Breakthrough time Aso Material thickness Aso			
	PVC (polyvinyl chloride) Direction of the second			
Eye protection:				
Eye protection: PPE: Characteristics:				
PPE:	Protective goggles against particle impacts.			
PPE: Characteristics:	Protective goggles against particle impacts. (mm): 0,35 Protective goggles against particle impacts. (CE» marking, category II. Eye protector against dust and smoke. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.			
PPE: Characteristics: CEN standards:	Protective goggles against particle impacts. (mm): 0,35 Protective goggles against particle impacts. (CE» marking, category II. Eye protector against dust and smoke. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should			
PPE: Characteristics: CEN standards: Maintenance:	Protective goggles against particle impacts. (mm): 0,35 Protective goggles against particle impacts. (CE» marking, category II. Eye protector against dust and smoke. EN 165, EN 166, EN 167, EN 168 Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses,			

(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



Version 1

Revision date: 30/01/2025

Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.
CEN standards:	EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.
PPE:	Anti-static safety footwear against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Solid - Dust Colour: white Odour: Odourless Odour threshold: Not available Melting point: Not available Freezing point: Not available Boiling point or initial boiling point and boiling range: Not applicable (Not relevant for this type of product) Flammability: No inflamable Lower explosion limit: Not available Upper explosion limit: Not available Flash point: Not applicable (Not relevant for this type of product) Auto-ignition temperature: Not available Decomposition temperature: Not available pH: 12 (100%) Kinematic viscosity: Not available Solubility: Not available Hydrosolubility: 6gr/L Liposolubility: Not available Partition coefficient n-octanol/water (log value): Not available Vapour pressure: Not available Absolute density: 1000 Relative density: 0.70+/-0.05 Relative vapour density: Not available Particle characteristics: <=0.5% Tamiz 200 µm

9.2 Other information

Not applicable/Not available due to the nature/properties of the producto

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



Version 1

Revision date: 30/01/2025

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

There are no tested data available on the product. Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin. Splashes in the eyes can cause serious and irreversible damage.

a) acute toxicity; Not conclusive data for classification.

b) skin corrosion/irritation; Product classified: Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;Product classified:Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;Product classified:Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure;
 Product classified:
 Specific target organ toxicity following a single exposure, Category 3: May cause respiratory irritation.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



Version 1

Revision date: 30/01/2025

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number or ID number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:	
ADR/RID:	Not classified as hazardous for transport.
IMDG:	Not classified as hazardous for transport.
ICAO/IATA:	Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



Version 1

Revision date: 30/01/2025

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Maritime transport in bulk according to IMO instruments.

Not classified as hazardous for transport.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC) VOC content (p/p): 1,075 % VOC content: 7,525 g/l

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
 3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 5.1. 	 Shall not be used in: ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, tricks and jokes, games for one or more participants, or any article intended to be used as such, even with ornamental aspects, Articles not complying with paragraph 1 shall not be placed on the market. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:

Kind of pollutant to water (Germany): nwg: Non-hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



grupo**puma**

Revision date: 30/01/2025

Complete text of the H phrases that appear in section 3:H315Causes skin irritation.H317May cause an allergic skin reaction.

- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.

Classification codes: Eye Dam. 1 : Serious eye damage, Category 1 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1 Skin Sens. 1B : Skin sensitiser, Category 1B

Changes regarding to the previous version:

- Modification of the symptoms (SECTION 4.2).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
65997-15-1	Cement, portland, chemicals	Registered
13397-24-5	Calcium sulfate hydrate	

Risk classification system NFPA 704:



Abbreviations and acronyms used:

AwSV: Facility Regulations for handling substances that are hazardous for the water.

CEN: European Committee for Standardization.

PPE: Personal protection equipment.

WGK: Water hazard classes.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

(in accordance with Regulation (EU) 2020/878)

PUMAPLAST EXTERIOR CERÁMICA



Version 1

Revision date: 30/01/2025

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.