

DECLARACION OF PERFORMANCES Nº: 860040

1. **Product:**
MORCEMCAL ACABADO EXTRAFINO
2. **Manufacturer:**
GRUPO PUMA SL with registered address:
C/ Conrado del Campo nº 2
29590 Campanillas (Málaga)
www.grupopuma.com
3. **Intended use:**
Smoothing mortar CR W0, based on natural hydraulic lime, for the realization of coatings and decoration, to be applied over Morcemcal Acabado in interiors and exteriors with an average thickness of 2 mm.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performances	Harmonized standards
Reaction to fire	Class A1	EN-998-1:2010
Water absorption	W0	
Water vapor diffusion coefficient:	$\mu \leq 7$	
Thermal conductivity (λ_{10} , dry)	0.30 W/mK (tabulated value)	
Durability	Evaluation based on provisions valid at the intended place of use of the mortar.	
Hazardous substances	See safety data sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 5.
This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.

Signed by and on behalf of the manufacturer:
Place and Date of issue: Málaga, 27/08/2020



Technical director: Jose A. Ferre Martínez



GRUPO PUMA SL
C/ Conrado del Campo nº - 29590 Campanillas (Málaga).
08
Nº.860040

EN 998-1

MORCEMCAL ACABADO EXTRAFINO

Smoothing mortar CR W0, based on natural hydraulic lime, for the realization of coatings and decoration, to be applied over Morcemcal Acabado in interiors and exteriors with an average thickness of 2 mm.

Reaction to fire : Class A1

Water absorption : W0

Water vapor diffusion coefficient : $\mu \leq 7$

Adhesion: $\geq 0.1 \text{N/mm}^2$ Breakage form B

Thermal conductivity ($\lambda_{10, \text{dry}}$) : 0.3 w/mK (tabulated value)

Durability: Evaluation based on provisions valid at the intended place of use of the mortar.