

DECLARATION OF PERFORMANCES


Nº: 600770-01

1. **Product:**
MORCEMDUR RASPADO
2. **Manufacturer:**
GRUPO PUMA ESPAÑA S.L located in: Avda.
AGRUPACIÓN CÓRDOBA, Núm. 17 14014
CÓRDOBA
www.grupopuma.com
3. **Intended use:**
OC CSIII W2 one-coat render mortar for façade finishing and protection against rain, with a scraped finish.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performance	Normas armonizadas
Reaction to fire	Type A1	EN 998-1:2018
Water absorption	W2	
Water permeability after conditioned weathering cycles	$\leq 1 \text{ ml/cm}^2$ after 48 hours	
Diffusion coefficient of water vapour	$\mu \leq 15$	
Thermal conductivity ($\lambda_{10,Dry}$)	PND	
Adhesion after conditioning weathering cycles	$\geq 0,3 \text{ N/mm}^2$ Shape breakage A/B	
Durability	Assessment based on adhesion and water permeability after conditioning weathering cycles.	
Hazardous substances	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the declared performance set out in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2, in accordance with Regulation (EU) No 305/2011.

Signed by and on manufacturer behalf:
Place and Date of issue: Córdoba, 04/03/2024



Technical Director: Jose A. Ferre Martínez



GRUPO PUMA ESPAÑA S.L
Avda. AGRUPACIÓN CÓRDOBA, Núm.17
14014 CÓRDOBA

18

MORCEMDUR RASPADO

Nº: 600770-01

EN 998-1

OC CSIII W2 one-coat render mortar for façade finishing and protection against rain,
with a scraped finish.

Reaction to fire	Type A1
Water absorption	W2
Water permeability after conditioned weathering cycles	$\leq 1 \text{ ml/cm}^2$ after 48 hours
Diffusion coefficient of water vapour	$\mu \leq 15$
Adhesion after conditioning weathering cycles	$\geq 0,3 \text{ N/mm}^2$ Shape breakage A/B
Durability	Assessment based on adhesion and water permeability after conditioning weathering cycles.
Hazardous substances	See safety datasheet