

DECLARATION OF PERFORMANCE

No.: 501040

1. **Product:**
PAVILAND RECRECIDO
2. **Distributor:**
GRUPO GRUPO PUMA ESPAÑA located at:
Avda. Agrupación Córdoba, 17 14014
CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Normal-setting cementitious flowing screed mortar, type CT-C25-F6-B2.0, for the preparation of floors subject to pedestrian traffic, for interior and exterior use, prior to the installation of floor coverings. Suitable for 10 to 60 mm thickness.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performances	Harmonized Technical Specification
Reaction to fire	A1 Type	EN 13813:2014
Hazardous substances emission	CT	
Weatherproof.	NPD	
Permeability to water vapour	NPD	
Compressive strength of concrete.	C25	
Flexural strength	F6	
Tensile strength	B2, 0	
Abrasion resistance	NPD	
Sound insulation:	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	

The performance of the product identified in point 1 conforms with the declared performance in point 5.
This Declaration of Performance is issued under the sole responsibility of the distributor indicated in point 2 in accordance with Regulation (EU) No 305/2011.

Signed by and on behalf of the manufacturer:
Place and date of issue: Córdoba, 11/02/26.



Technical Director: Jose A. Ferre Martínez



GRUPO PUMA ESPAÑA, S.L
 Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
 14014 CÓRDOBA

26

PAVILAND RECRECIDO

Nº. 501040

EN 13813

Normal-setting cementitious flowing screed mortar, type CT-C25-F6-B2.0, for the preparation of floors subject to pedestrian traffic, for interior and exterior use, prior to the installation of floor coverings.

Suitable for 10 to 60 mm thickness.

Reaction to fire	A1 Type
Hazardous substances emission	CT
Compressive strength of concrete.	C25
Flexural strength	F6
Tensile strength	B2, 0