

DECLARATION OF PERFORMANCES

Nº: 105286

1.- Product: PEGOLAND PROFESIONAL FLEX BLANCO

2.-Manufacturer: GRUPO PUMA SL with registered address at: Avda. Agrupación Córdoba 17,14014 Córdoba www.grupopuma.com

3.-Intended use: Cement based improved adhesive, highly deformable, non slip and with extended open time for the application of interior and exterior pavements and claddings.

4.-Evaluation System: 3

5.- Notified bodies: Tests type nº 0201-01-2014-12269 have been carried out dated November 12, 2015 in CEMOSA No. 1377 (Málaga)

6.-Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN-12004:2007 +A1:2012
Adherence: Initial tensile adhesion strength	$\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.

This declaration of features is issued under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf:

Place and date of issue: Málaga, 28/05/2019



Technical Director: Jose A. Ferre Martínez



GRUPO PUMA SL
Avda Agrupación Córdoba 17
14014 Córdoba
15
Nº: 105286

EN 12004: 2007+A1:2012

PEGOLAND PROFESIONAL FLEX BLANCO

Cement based improved adhesive, highly deformable, non slip and with extended open time for the application of interior and exterior pavements and claddings.

- **Reaction to fire:** Class E

- **Adherence:**

Initial tensile adhesion strength: $\geq 1\text{N/mm}^2$

- **Durability:**

- **Tensile adhesion after water immersion:** $\geq 1\text{N/mm}^2$
- **Tensile adhesion after heat aging:** $\geq 1\text{N/mm}^2$
- **Tensile adhesion after freeze/thaw cycles:** $\geq 1\text{N/mm}^2$

- **Hazardous substances:** See safety datasheet