

DECLARATION OF PERFORMANCES Nº: 210078

1.- Product:

MORCEMGROUT 500

2.-Intended use:

Products for concrete repair and protection. High-strength mortar for backfilling and anchoring of machinery, leveling of supports and bridges, application thickness from 20 to 200 mm. Principle 4, method 4.1 according to 1504-6 and 4.2 according to 1504-9.

3.-Manufacturer:

GRUPO PUMA SL with registered address: Avda Agrupación Córdoba nº 17 ,14014 Córdoba www.grupopuma.com

4.-System of evaluation and verification of the constancy of product performance (EVCP):

2+ plus 4

5.-Notified bodies:

Applus nº 0370, Production Control Certificate of Conformity nº0370-CPR-2578

6.-Declared performances

Essential characteristics	Performances	Harmonised standards	Harmonized Technical Specification
Tear-off resistance, displacement	≤0.06 mm	EN 1881	EN-1504-6:2006
Chloride ion content	≤0.05%	EN 1015-17	
Hazardous substances	See Safety Data Sheet		
Reaction to fire	A1	EN 13501	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6 This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 3, in accordance with Regulation (EU) No 305/2011.

Signed by and on behalf of the manufacturer:
Place and Date of issue: Córdoba, 8/08/2018

Technical director: Jose A. Ferre Martínez





0370

GRUPO PUMA SL
Avda. Agrupación Córdoba nº 17 ,14014 Córdoba
16
Nº: 210078

0370-CPR-2578

1504-6

MORCEMGROUT 500

High-strength mortar for backfilling and anchoring of machinery, leveling of supports and bridges, application thickness from 20 to 200 mm.

Tear-off resistance, displacement: ≤ 0.6 mm at a load of 75KN

Chloride ion content : $\leq 0.05\%$

Reaction to fire: A1