

DECLARATION OF PERFORMANCES

Nº: 501869-01

1. Product:

PAVILAND SOLERA R AUTONIVELANTE

2. Manufacturer:

GRUPO PUMA ESPAÑA S.L located in:
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com

3. Intended use:

CT C25 F5 B1 5 type, fast-setting, self-levelling, screed mortar for interior floors, 50 mm when adhered and 100 mm when non-adhered.

4. Evaluation system:

4

5. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type E	EN 13813:2014
Emission of harmful substances	CT	
Water permeability	NPD	
Water vapour permeability	NPD	
Compressive strength	C25	
Flexural strength/ Resistance to bending	F5	
Traction resistance	B1,5	
Wear strength	NPD	
Sound insulation	NPD	
Acoustic absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5.

The present declaration of performance is issued under the sole responsibility of manufacturer stated in point 2, in accordance with Regulation (UE) nº 305/2011.

Signed by and on manufacturer behalf:

Place and date of issue: Córdoba, 14/07/23



Technical director: Jose A. Ferre Martínez



GRUPO PUMA ESPAÑA, S.L
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA

16

PAVILAND SOLERA R AUTONIVELANTE

Nº: 501869-01

EN 13813

CT C25 F5 B1 5 type, fast-setting, self-levelling, screed mortar for interior floors, 50 mm when adhered and 100 mm when non-adhered.

Reaction to fire	Type E
Emission of harmful substances	CT
Compressive strength	C25
Flexural strength/ Resistance to bending	F5
Traction resistance	B1,5
Hazardous substances	See safety datasheet