

DECLARATION OF PERFORMANCES

Nº: 120032-158

1. **Product:**
PEGOLAND ESPECIAL GRIS
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Normal setting cementitious adhesive, with reduced slip and extended open time, Pegoland Especial Gris, for bonding pieces with absorption >3% and glass mosaics, on interior walls and floors, and exterior floors. Suitable for the installation of low absorption ($\leq 3\%$) tiles in interior residential and public pedestrian floors and walls, if the length of the longer side of the tile is ≤ 30 cm.
4. **Evaluation system:**
3
5. **Notified bodies:**
Type tests were conducted under report number 71383, 71416, 71426, 71447, 75449, 79618 and 80108 dated March, April, June, and September 2004 at CEMOSA (No. 1377, Málaga) and 5029472 and 5026638 dated July and September 2005 at APPLUS (Nº 0370, Barcelona), obtaining identical product performance results for all manufacturing plants.
6. **Declared performances:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire:	E Class	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after heat ageing - Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performance of the product identified in point 1 conforms with the declared performance in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on manufacturer's behalf:
Place and date of issue: Málaga, 07/01/2025



Technical Director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 04	
PEGOLAND ESPECIAL GRIS Nº: 120032-158 EN-12004:2007+A1:2012 Normal setting cementitious adhesive, with reduced slip and extended open time. Suitable for interior walls and floors and for exterior floors.	
Reaction to fire:	E Class
Adhesion: - Initial tensile adhesion strength	≥ 0,5 N/mm ²
Durability: - Tensile adhesion strength after water immersion: - Tensile adhesion strength after heat ageing: - Tensile adhesion strength after freeze–thaw cycles:	≥ 0,5 N/mm ² ≥ 0,5 N/mm ² ≥ 0,5 N/mm ²
Hazardous substances:	See safety datasheet