

DECLARATION OF PERFORMANCE

Nº: 500537

1. **Product:**
PAVILAND FIBRA
2. **Distributor:**
GRUPO PUMA ESPAÑA S.L located in: Avda.
Agrupación Córdoba, 17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Polymeric fibres for concrete. For other uses in concrete, mortar, and grout.
4. **Evaluation system:**
3
5. **Notified bodies:**
Laboratory 2211 – Itecons Pólo II Universidade de Coimbra Rua Pedro Hispano, s/n 3030-289 Coimbra
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Fibre classification	Ia Class	EN 14889-2: 2006
Tensile strength (tenacity)	20,5 cN/tex	
Length	12 mm	
Melting point	163,6 °C	
Ignition point	Not detected	
Effect on the consistency of concrete at 600 g/m ³	Type Vêvê: V3	

The performance of the product identified in point 1 conforms with the declared performance in point 6.
This Declaration of Performance is issued under the sole responsibility of the manufacturer indicated in point 2 in accordance with Regulation (EU) No 305/2011.

Signed by and on manufacturer behalf:
Place and date of issue: Córdoba, 16/02/26



Technical Director: Jose A. Ferre Martínez

CE	
GRUPO PUMA ESPAÑA S.L. Avda. Agrupación Córdoba, 17 14014 CÓRDOBA	
26	
PAVILAND FIBRA	
Nº: 500537	
EN 14889-2	
Polymeric fibres for concrete. For other uses in concrete, mortar, and grout.	
Fibre classification	Type Ia
Tensile strength (tenacity)	20,5 cN/tex
Length	12 mm
Melting point	163,6 °C
Ignition point	Not detected
Effect on the consistency of concrete at 600 g/m³	Type Vêvê: V3