

## DECLARATION OF PERFORMANCES

### Nº: 105285-399

1. **Product:**  
PEGOLAND GEL S2
2. **Manufacturer:**  
GRUPO PUMA SL located in:  
Calle Conrado del Campo, nº2  
29590 Campanillas (Malaga)  
[www.grupopuma.com](http://www.grupopuma.com)
3. **Intended use:** Improved highly deformable cementitious adhesive with reduced slip and extended open time, PEGOLAND GEL S2, for gluing floors and walls, interiors and exteriors, especially for facades, pavements of large surfaces, large-format and/or low-thickness pieces, underfloor heating, overlays, chambers refrigerators, swimming pools and on cementitious waterproofing.
4. **Evaluation system:**  
3
5. **Notified bodies:** Type tests nº 01-15/000911/1, dated February 2015, have been carried out in CEMOSA nº 1377 (Málaga) and nº18/14017-539 dated February 2018, 18/16382-187, 18/16354-752 dated March 2018, in APPLUS nº 0370 (Barcelona) obtaining the same product results for all factories.
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
<b>Reaction to fire:</b>	Type E	EN-12004:2007+A1:2012
<b>Adhesion:</b> - Initial tensile adhesion strength	$\geq 1 \text{ N/mm}^2$	
<b>Durability:</b> - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$	
<b>Hazardous substances</b>	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.  
This declaration of features is issued under the sole responsibility of manufacturer stated in point 2.  
Signed by and on manufacturer behalf.  
Place and date of issue: Malaga, 29/08/2022



Technical director: José A. Ferre Martínez



0370, 1377

GRUPO PUMA SL  
C/ Conrado del Campo nº 2 - 29590 Campanillas (Málaga).  
15

**PEGOLAND GEL S1**  
**Nº: 100592-394**  
**EN 12004:2007+A1:2012**

Improved highly deformable cementitious adhesive with slip reduced and extended open time, for floors, walls and facades, indoor and outdoor application.

**Reaction to fire:** Type E

**Adhesion:**

- Initial tensile adhesion strength  $\geq 1 \text{ N/mm}^2$

**Durabilité:**

- Tensile adhesion after water immersion  $\geq 1 \text{ N/mm}^2$
- Tensile adhesion after heat aging  $\geq 1 \text{ N/mm}^2$
- Tensile adhesion after freeze/thaw cycles  $\geq 1 \text{ N/mm}^2$

**Hazardous substances:** See safety datasheet