

DECLARATION OF PERFORMANCE

Nº.: 125235-123


1. **Product:**
PEGOLAND UNO GRIS
2. **Manufacturer:**
GRUPO PUMA ESPAÑA located at:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Normal-setting cementitious adhesive Pegoland Uno Gris, for tile adhesion with medium to high absorption in interior and exterior floors and interior walls.
4. **Evaluation system:**
3
5. **Notified bodies:**
The following type tests were carried out: Nos. 1/1536/001/020, 1/3448/002/016 and 1/1541/001/021, dated May and October 2009; No. 1/1541/001/021, dated March 2010; Nos. 01-11/017873/1 and 01-11/005233/1, dated May and November 2011; No. 01-16/019958/1, dated June 2016; Nos. 01-18/000692/1 and 01-18/002353/1, dated December 2017; No. 01-19/023462/1, dated May 2019; and Nos. 001-23/024182/1, 001-23/024189/1 and 001-23/024173/1, dated June 2023, at CEMOSA No. 1377 (Málaga); and Nos. 09/1074-3123 and 09/1106-3219, dated January 2010, and No. 12/5902-2024, dated March 2013, at APPLUS No. 0370 (Barcelona), obtaining the same product performance results for all manufacturing plants.
6. **Declared performances:**

Essential characteristics	Performances	Harmonized Technical Specification
Reaction to fire:	E Class	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after heat ageing - Tensile adhesion strength after freeze- thaw cycles	$\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$	
Hazardous substances:	See safety data sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on behalf of the manufacturer:

Place and date of issue: Málaga, 07/01/2025



Technical Director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 09	
PEGOLAND UNO GRIS no. 125235-123 EN-12004:2007+A1:2012 Normal setting, cementitious adhesive for the installation of interior and exterior floors and interior walls.	
Reaction to fire:	E Class
Adhesion: - Initial tensile adhesion strength:	≥ 0,5 N/mm ²
Durability: - Tensile adhesion strength after water immersion:	≥ 0,5 N/mm ²
- Tensile adhesion strength after heat ageing:	≥ 0,5 N/mm ²
- Tensile adhesion strength after freeze-thaw cycles:	≥ 0,5 N/mm ²
Hazardous substances:	See safety data sheet