

DECLARATION OF PERFORMANCE

No.: 860037

1. **Product:**
MORCEMCAL MURO
2. **Manufacturer:**
GRUPO PUMA ESPAÑA located at: Avda.
AGRUPACIÓN CÓRDOBA, Núm.17 14014
CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Prescribed general-purpose masonry mortar (G), based on natural hydraulic lime, for the construction and repair of walls and masonry.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performances	Harmonized Technical Specification
Mix proportions (by volume)	Cement: 0% Lime: 47% Aggregates: 53%	EN 998-2:2018
Adhesion	NPD	
Chloride content	NPD	
Reaction to fire	A1 Type	
Water absorption	NPD	
Water vapour permeability coefficient	$\mu \leq 6$	
Thermal Conductivity ($\lambda_{10 \text{ dry}}$)	NPD	
Durability:	NPD	
Hazardous substances	Consult safety data sheet	

The performance of the product identified in point 1 conforms with the declared performance in point 5.
This Declaration of Performance is issued under the sole responsibility of the manufacturer indicated in point 2 in accordance with Regulation (EU) No 305/2011.

Signed by and on behalf of the manufacturer:
Place and date of issue: Córdoba, 31/08/26.



Technical Director: Jose A. Ferre Martínez


GRUPO PUMA ESPAÑA, S.L Avda. Agrupación Córdoba, Núm.17 14014 CÓRDOBA 26
MORCEMCAL MURO No.: 860037 EN 998-2 Prescribed general-purpose masonry mortar (G), based on natural hydraulic lime, for the construction and repair of walls and masonry.
Mix proportions (by volume): Cement 0% Lime: 47% Aggregates: 53%
Reaction to fire Class A1
Water vapour permeability coefficient $\mu \leq 6$