

DECLARATION OF PERFORMANCES Nº: 860006

1. **Product:**
MORCEMCAL BASE
2. **Manufacturer:**
GRUPO PUMA SL with registered address:
Avda. AGRUPACIÓN CÓRDOBA, Núm.17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Colored plastering mortar CR CSII W0, based on natural hydraulic lime, for exterior and interior plastering and rendering, with thicknesses between 0.5 and 1.5 cm.
4. **Evaluation system:**
4
5. **Performances declared:**

Essential characteristics	Performances	Harmonized technical specifications
Adhesion	≥0.3 N/mm ² Breakage form A/B	EN-998-1:2010
Reaction to fire	A1	
Water absorption	W0	
Water vapor permeability	≤μ 6	
Thermal conductivity (λ10, dry)	NPD	
Durability	NPD	
Hazardous substances:	See Safety Data Sheet	

The performance of the product identified in item 1 is in conformity with the performance declared in item 5
 This declaration of performance is issued under the sole responsibility of the manufacturer indicated in item 2
 Signed by and on behalf of the manufacturer:
 Place and Date of issue: Córdoba, 31/01/2019



Technical director: Jose A. Ferre Martínez



GRUPO PUMA SL
 Avda. AGRUPACIÓN CÓRDOBA, Núm.17
 14014 CÓRDOBA
 11

MORCEMCAL BASE

Nº: 860006

EN 998-1

Colored plastering mortar CR CSII W0, based on natural hydraulic lime, for exterior and interior plastering and rendering, with thicknesses between 0.5 and 1.5 cm.

Reaction to fire	Class A1
Water absorption	W0
Water vapor permeability	$\mu \leq 6$
Adhesion	$\geq 0.3 \text{ N/mm}^2$ Breakage form A/B