

DECLARATION OF PERFORMANCES

Nº: 501864-01

1. **Product:**
NIVELAND 30R
2. **Manufacturer:**
GRUPO PUMA ESPAÑA, S.L. located in:
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Fiber-reinforced, fast-setting self-levelling cement-based mortar, type CT C30 F6 B1.5, for the preparation of interior floors and the installation of light floor coverings such as ceramic tiles, parquet, carpet, etc., for thicknesses going from 2 to 30 mm.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	E Class	EN 13813:2014
Emission of harmful substances	CT	
Water permeability	NPD	
Water vapour permeability	NPD	
Compressive strength	C30	
Flexural strength	F6	
Tensile strength	B1,5	
Acoustic insulation	NPD	
Acoustic absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Hazardous substances	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the declared performance in point 5.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2, in accordance with Regulation (EU) No 305/2011.

Signed by and on manufacturer behalf:
Place and date of issue: Córdoba, 08/04/2026



Technical Director: Jose A. Ferre Martínez

CE	
GRUPO PUMA ESPAÑA, S.L Avda. AGRUPACIÓN CÓRDOBA, Núm. 17 14014 CÓRDOBA	
26	
NIVELAND 30R Nº: 501864-01 EN 13813 Fiber-reinforced, fast-setting self-levelling cement-based mortar, type CT C30 F6 B1.5, for the preparation of interior floors and the installation of light floor coverings such as ceramic tiles, parquet, carpet, etc., for thicknesses from 2 to 30 mm.	
Reaction to fire	E Class
Emission of harmful substances	CT
Compressive strength	C30
Flexural strength	F6
Tensile strength	B1,5
Hazardous substances	See safety datasheet