

## DECLARATION OF PERFORMANCES

### Nº: 110132-152

1. **Product:**  
PEGACOL BLANCO
2. **Manufacturer:**  
GRUPO PUMA SL located in:  
Calle Conrado del Campo, nº2  
29590 Campanillas (Malaga)  
[www.grupopuma.com](http://www.grupopuma.com)
3. **Intended use:** Cementitious adhesive, for gluing coatings and flooring indoors, with a degree of absorption >3%, for floors and walls, not suitable for outdoor application.
4. **Evaluation system:**  
3
5. **Notified bodies:** Type tests nº 71361, 71376, 71390, 71392, 71418 ,71438, 71473, 71477 71482, 73825, dated February, March, April and May 2004 and 2802735 April 2008 have been carried out in CEMOSA nº 1377 (Málaga), and tests nº 06/31211946, 09/1081-3153 dated April 2006 and January 2010 have been carried out in APPLUS nº 0370 (Barcelona), obtaining the same results of the product for all factories.
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
<b>Reaction to fire:</b>	Clase A1fl y A1	EN-12004:2007+A1:2012
<b>Adhesion:</b> - Initial tensile adhesion strength	≥ 0.5 N/mm <sup>2</sup>	
<b>Durability:</b> - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	≥ 0.5 N/mm <sup>2</sup>  NPD  NPD	
<b>Hazardous substances</b>	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.  
This declaration of features is issued under the sole responsibility of manufacturer stated in point 2.  
Signed by and on manufacturer behalf.  
Place and date of issue: Malaga, 01/07/2015



Technical director: José A. Ferre Martínez



0370, 1377

GRUPO PUMA SL  
C/ Conrado del Campo nº 2 - 29590 Campanillas (Málaga).  
15

**PEGACOL BLANCO**  
**Nº: 110132-152**  
**EN 12004: 2007+A1:2012**

Cementitious adhesive, for gluing coatings and flooring indoors, with a degree of absorption >3%, for floors and walls, not suitable for outdoor application.

**Reaction to fire:**

A1fl  
A1

**Adhesion:**

- Initial tensile adhesion strength  $\geq 0.5 \text{ N/mm}^2$

**Durabilité:**

- Tensile adhesion after water immersion  $\geq 0.5 \text{ N/mm}^2$

**Hazardous substances:**

See safety datasheet