

DECLARATION OF PERFORMANCES

Nº: 150080

1.- Product: TRADITERM PROYECTABLE

2.-Intended use: Coating and cladding mortar of general purpose, GP, used in the adhesion and coating of insulating plates made of expanded polystyrene, graphite EPS and mineral wool, for thermal insulation systems on the outside, ETICS, both in new construction and rehabilitation. Rainwater impermeable and water vapor permeable.

3.-Manufacturer: GRUPO PUMA SL with registered address at: Avda. Agrupación Córdoba 17,14014 Córdoba www.grupopuma.com

4.-Evaluation System: 4

5.-Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class A1	EN-998-1:2010
Water absorption	W2	
Diffusion coefficient of water vapour	$\mu \leq 15$	
Thermal conductivity :(λ_{10} ,dry)	0.33W/mK (tabulated value)	
Adhesion	$\geq 0.8\text{N/mm}^2$ Breakage method A/B	
Durability	NPD	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5.

This declaration of features is issued under the sole responsibility of manufacturer stated in point 3

Signed by and on manufacturer behalf:

Place and date of issue: Málaga, 28/05/2019



Technical Director: Jose A. Ferre Martínez



GRUPO PUMA SL
Avda Agrupación Córdoba 17
14014 Córdoba
14
Nº: 150080

EN 998-1

TRADITERM PROYECTABLE

Coating and cladding mortar of general purpose, GP, used in the adhesion and coating of insulating plates made of expanded polystyrene, graphite EPS and mineral wool, for thermal insulation systems on the outside, ETICS, both in new construction and rehabilitation. Rainwater impermeable and water vapor permeable

- Reaction to fire:** Class A1
- Water absorption:** W2
- Diffusion coefficient of water vapour:** $\mu \leq 15$
- **Thermal conductivity:** $(\lambda_{10, dry}) = 0.33 \text{ W/mK}$
- Adhesion:** $\geq 0.8 \text{ N/mm}^2$ Breakage method A/B