

## DECLARATION OF PERFORMANCES

### Nº: 120032-158

1. **Product:**  
PEGOLAND ESPECIAL GRIS
  
2. **Manufacturer:**  
GRUPO PUMA SL with address at:  
C) ) Conrado del Campo nº  
29590 Campanillas (Málaga)  
www.grupopuma.com
  
3. **Intended use:**  
Normal setting cementitious adhesive with reduced slip and extended open time, Pegoland Especial Gris, for bonding pieces with absorption > 3 % and vitreous mosaics, in tiling, interior flooring, skirting boards and exterior flooring.
  
4. **Evaluation system:**  
3
  
5. **Notified bodies:**  
The type tests nº 71383, 71416, 71426, 71447, 75449, 79618, 80108 dated March, April, June, September 2004, and nº 2011/1/2012/252 dated January 2012, in CEMOSA nº 1377 (Málaga) and nº 5029472, 5026638 dated July and September 2005 in APPLUS nº 0370 (Barcelona), obtaining the same results of the product for all the factories.
  
6. **Declared performances:**

Essential characteristics	Performances	Harmonized technical specifications
<b>Reaction to fire:</b>	Class E	EN-12004:2007+A1:2012
<b>Adherence:</b> - Initial tensile adhesion	≥ 0,5N/mm <sup>2</sup>	
<b>Durability:</b> - Tensile adhesion after immersion in water - Tensile adhesion after thermal aging - Tensile adhesion after freeze/thaw cycles	≥ 0,5N/mm <sup>2</sup> ≥ 0,5N/mm <sup>2</sup> ≥ 0,5N/mm <sup>2</sup>	
<b>Hazardous substances:</b>	See Safety Data Sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6  
This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.  
Signed by and on behalf of the manufacturer:

Place and Date of issue: Málaga, 01/07/2015



Technical director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA SL C) Conrado del Campo nº 2 29590 Campanillas (Málaga) 04	
<b>PEGOLAND ESPECIAL GRIS</b> <b>Nº: 120032-158</b> <b>EN 12004: 2007 + A1:2012</b> Normal setting cementitious adhesive with reduced slip and extended open time, for floors and walls, interior and exterior application.	
<b>Reaction to fire:</b>	Class E
<b>Adherence:</b>	
- Initial tensile adhesion:	$\geq 0,5\text{N/mm}^2$
<b>Durability:</b>	
- Tensile adhesion after immersion in water	$\geq 0,5\text{N/mm}^2$
- Tensile adhesion after thermal aging	$\geq 0,5\text{N/mm}^2$
- Tensile adhesion after freeze/thaw cycles	$\geq 0,5\text{N/mm}^2$
<b>Hazardous substances:</b>	See safety data sheet