# Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

# **PAVILAND TOP PU COLOR MATE (COMP. B)**



# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** PAVILAND TOP PU COLOR MATE (COMP. B)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Coatings for decorative jointless flooring. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

#### 1.3 Details of the supplier of the safety data sheet:

GRUPO PUMA SL

AVDA. AGRUPACIÓN CÓRDOBA, NUM. 17 14014 CÓRDOBA - CÓRDOBA - ESPAÑA

Phone.: +34 901 11 69 12 - Fax: +34 957 44 19 92

fds@grupopuma.com http://www.grupopuma.com

**1.4** Emergency telephone number: 901 11 69 12 (Horario de atención: 08:30 – 13:30 y de 16:00 – 19:00)

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

#### 2.2 Label elements:

#### CLP Regulation (EC) No 1272/2008:

#### Warning





#### **Hazard statements:**

Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Sens. 1: H317 - May cause an allergic skin reaction STOT SE 3: H335 - May cause respiratory irritation STOT SE 3: H336 - May cause drowsiness or dizziness

#### **Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish

P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

#### **Supplementary information:**

EUH066: Repeated exposure may cause skin dryness or cracking EUH204: Contains isocyanates. May produce an allergic reaction

#### Substances that contribute to the classification

 $\hbox{N-butyl acetate; Hexamethylene diisocyanate, oligomers; Aromatic hydrocarbons, C8}\\$ 

## 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Date of compilation: 10/06/2019 Revised: 10/06/2019 Version: 2 (Replaced 1) Page 1/12

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

# **PAVILAND TOP PU COLOR MATE (COMP. B)**



# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Non-applicable

#### 3.2 Mixture:

Chemical description: Isocyanate/s

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration	
CAS:	123-86-4	N-butyl acetate□¹□	N-butyl acetate□¹□			
Index:	EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29- XXXX		Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	<b>(1)</b>	25 - <50 %	
CAS:	28182-81-2	Hexamethylene diisocyanate, oligomers□¹□				
Index:	EC: 931-274-8 Index: Non-applicable REACH: 01-2119485796-17- XXXX Regulation 1272/2008		Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	<b>(1)</b>	25 - <50 %	
CAS:	108-65-6	2-methoxy-1-methyl	ethyl acetate□²□	ATP ATP01		
EC: Index: REACH:	203-603-9 607-195-00-7 01-2119475791-29- XXXX	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning	<b>®</b>	2,5 - <10 %	
CAS:	90989-38-1	Aromatic hydrocarbo	ns, C8□¹□	ATP ATP01		
Index:	EC: 292-694-9 Index: 648-010-00-X REACH: 01-2119486136-34- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	♦	2,5 - <10 %	

 $<sup>\</sup>square^{1}\square$  Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

# **SECTION 4: FIRST AID MEASURES**

## 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### Bv skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

## 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

# 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

# SECTION 5: FIREFIGHTING MEASURES

Date of compilation: 10/06/2019 Revised: 10/06/2019 Version: 2 (Replaced 1) Page 2/12

<sup>□</sup>²□ Substance with a Union workplace exposure limit

# Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

# **PAVILAND TOP PU COLOR MATE (COMP. B)**



# SECTION 5: FIREFIGHTING MEASURES (continued)

## 5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers ( $CO\square$ ). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

## 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

# **SECTION 7: HANDLING AND STORAGE**

#### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

# 7.2 Conditions for safe storage, including any incompatibilities:

Date of compilation: 10/06/2019 Revised: 10/06/2019 Version: 2 (Replaced 1) Page 3/12

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

# PAVILAND TOP PU COLOR MATE (COMP. B)



# SECTION 7: HANDLING AND STORAGE (continued)

A.- Technical measures for storage

Minimum Temp.:  $10 \, ^{\circ}\text{C}$  Maximum Temp.:  $30 \, ^{\circ}\text{C}$ 

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	En	vironmental limits	
2-methoxy-1-methylethyl acetate	IOELV (8h)	50 ppm	275 mg/m <sup>3</sup>
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>

# **DNEL (Workers):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-658-1	Inhalation	960 mg/m <sup>3</sup>	960 mg/m <sup>3</sup>	480 mg/m <sup>3</sup>	480 mg/m <sup>3</sup>
Hexamethylene diisocyanate, oligomers	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 28182-81-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 931-274-8	Inhalation	Non-applicable	1 mg/m³	Non-applicable	0,5 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	153,5 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	275 mg/m <sup>3</sup>	Non-applicable
Aromatic hydrocarbons, C8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 90989-38-1	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 292-694-9	Inhalation	Non-applicable	Non-applicable	77 mg/m³	Non-applicable

# **DNEL (General population):**

		Short e	Short exposure Long exposure		xposure
Identification		Systemic	Local	Systemic	Local
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 204-658-1	Inhalation	859,7 mg/m <sup>3</sup>	859,7 mg/m <sup>3</sup>	102,34 mg/m <sup>3</sup>	102,34 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable
CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	54,8 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	Non-applicable
Aromatic hydrocarbons, C8	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 90989-38-1	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
EC: 292-694-9	Inhalation	Non-applicable	Non-applicable	14,8 mg/m <sup>3</sup>	Non-applicable

# PNEC:

Identification				
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,0903 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0981 mg/kg

Date of compilation: 10/06/2019 Revised: 10/06/2019 Version: 2 (Replaced 1) **Page 4/12** 



# PAVILAND TOP PU COLOR MATE (COMP. B)



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Hexamethylene diisocyanate, oligomers	STP	38,3 mg/L	Fresh water	0,127 mg/L
CAS: 28182-81-2	Soil	53182 mg/kg	Marine water	0,0127 mg/L
EC: 931-274-8	Intermittent	1,27 mg/L	Sediment (Fresh water)	266700 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	26670 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,0635 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Aromatic hydrocarbons, C8	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 90989-38-1	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 292-694-9	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg

#### 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

### B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

# C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

<sup>&</sup>quot;As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

# D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

#### E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

Date of compilation: 10/06/2019 Revised: 10/06/2019 Version: 2 (Replaced 1) Page 5/12



# PAVILAND TOP PU COLOR MATE (COMP. B)



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN ISO 13287:2012 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>*</b> T	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

#### **VOLATILE ORGANIC COMPOUNDS**

With regard to Directive 2004/42/EC:

Paviland Top PU Color Mate (82 % Comp. A + 18 % Comp. B): V.O.C. density at 20  $^{\circ}$ C < 500 g/L. EU limit for the product (Cat. A.J): 500 g/L (2010)

(COMP. A: V.O.C. density at 20 °C: 392,81 g/L; COMP. B: V.O.C. density at 20 °C: 605,15 g/L)

#### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

# Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Not available

Not available

Not available

Not available

Not available

Non-applicable \*

# Volatility:

Boiling point at atmospheric pressure:

Vapour pressure at 20 °C:

Vapour pressure at 50 °C:

Non-applicable \*

Evaporation rate at 20 °C:

Non-applicable \*

# **Product description:**

Density at 20 °C: 960 - 1000 kg/m<sup>3</sup> Relative density at 20 °C: Non-applicable \* Dynamic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 40 °C: Non-applicable \* Concentration: Non-applicable \* pH: Non-applicable \* Vapour density at 20 °C: Non-applicable \* Partition coefficient n-octanol/water 20 °C: Non-applicable \* Solubility in water at 20 °C: Non-applicable \* \*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/06/2019 Revised: 10/06/2019 Version: 2 (Replaced 1) Page 6/12



# **PAVILAND TOP PU COLOR MATE (COMP. B)**



# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Solubility properties:

Decomposition temperature:

Melting point/freezing point:

Explosive properties:

Oxidising properties:

Non-applicable \*

Non-applicable \*

Non-applicable \*

Flammability:

Flash Point: ≈26 °C

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Non-applicable \*

Not available

Not available

**Explosive:** 

Lower explosive limit:

Upper explosive limit:

Non-applicable \*

Non-applicable \*

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable \*

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

## 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Contact with air Increase in temperature		Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others	
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases	

# 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

# 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

# **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

Date of compilation: 10/06/2019 Revised: 10/06/2019 Version: 2 (Replaced 1) Page 7/12

# Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

# PAVILAND TOP PU COLOR MATE (COMP. B)



# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
  - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
  - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

# Other information:

Non-applicable

#### Specific toxicology information on the substances:

Identification	Acu	Acute toxicity	
Aromatic hydrocarbons, C8	LD50 oral	3223 mg/kg	Rat
CAS: 90989-38-1	LD50 dermal	1100 mg/kg (ATEi)	
EC: 292-694-9	LC50 inhalation	11 mg/L (4 h) (ATEi)	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
N-butyl acetate	LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat
Hexamethylene diisocyanate, oligomers	LD50 oral	5100 mg/kg	Rat
CAS: 28182-81-2	LD50 dermal	Non-applicable	
EC: 931-274-8	LC50 inhalation	11 mg/L (4 h) (ATEi)	

# SECTION 12: ECOLOGICAL INFORMATION



# **PAVILAND TOP PU COLOR MATE (COMP. B)**



# SECTION 12: ECOLOGICAL INFORMATION (continued)

The experimental information related to the eco-toxicological properties of the product itself is not available

# 12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
N-butyl acetate	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
CAS: 123-86-4	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
EC: 204-658-1		675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Hexamethylene diisocyanate, oligomers		Non-applicable		
CAS: 28182-81-2	EC50	Non-applicable		
EC: 931-274-8	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		

### 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability		
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable	
CAS: 123-86-4	COD	Non-applicable	Period	5 days	
EC: 204-658-1	BOD5/COD	0.79	% Biodegradable	84 %	
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L	
CAS: 108-65-6	COD	Non-applicable	Period	8 days	
EC: 203-603-9	BOD5/COD	Non-applicable	% Biodegradable	100 %	

#### 12.3 Bioaccumulative potential:

Identification	Bioacc	Bioaccumulation potential		
N-butyl acetate	BCF	4		
CAS: 123-86-4	Pow Log	1.78		
EC: 204-658-1	Potential	Low		
2-methoxy-1-methylethyl acetate	BCF	1		
CAS: 108-65-6	Pow Log	0.43		
EC: 203-603-9	Potential	Low		

#### 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
N-butyl acetate	Koc	Non-applicable	Henry	Non-applicable
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable

# 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

#### 12.6 Other adverse effects:

Not described

# SECTION 13: DISPOSAL CONSIDERATIONS

# 13.1 Waste treatment methods:

	Code	Description	Waste class (Regulation (EU) No 1357/2014)	
08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substants		waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous	

#### Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising

## Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

# Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

# **PAVILAND TOP PU COLOR MATE (COMP. B)**



# SECTION 13: DISPOSAL CONSIDERATIONS (continued)

## Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# **SECTION 14: TRANSPORT INFORMATION**

# Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



**14.1 UN number:** UN1139

**14.2 UN proper shipping name:** COATING SOLUTION (includes surface treatments or coatings used

for industrial or other purposes such as vehicle under coating, drum

or barrel lining)

14.3 Transport hazard class(es):

Labels: 3 **14.4 Packing group:** III

14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: Non-applicable

Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Transport in bulk according

to Annex II of Marpol and the IBC Code:

Non-applicable

# Transport of dangerous goods by sea:

With regard to IMDG 38-16:

**14.1 UN number:** UN1139

**14.2 UN proper shipping name:** COATING SOLUTION (includes surface treatments or coatings used

for industrial or other purposes such as vehicle under coating, drum

or barrel lining)

14.3 Transport hazard class(es): 3

Labels: 3

**14.4 Packing group:** III **14.5 Environmental hazards:** No

14.6 Special precautions for user

Special regulations: Non-applicable

EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Non-applicable

14.7 Transport in bulk according Non-applicable

to Annex II of Marpol and

the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2019:

Date of compilation: 10/06/2019 Revised: 10/06/2019 Version: 2 (Replaced 1) Page 10/12

# Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

# **PAVILAND TOP PU COLOR MATE (COMP. B)**

3



# SECTION 14: TRANSPORT INFORMATION (continued)



UN1139 14.1 UN number:

COATING SOLUTION (includes surface treatments or coatings used 14.2 UN proper shipping name:

for industrial or other purposes such as vehicle under coating, drum

or barrel lining)

14.3 Transport hazard class(es):

Labels: 3

14.4 Packing group: III 14.5 Environmental hazards: No

14.6 Special precautions for user

Physico-Chemical properties:

14.7 Transport in bulk according

the IBC Code:

see section 9 Non-applicable

to Annex II of Marpol and

# **SECTION 15: REGULATORY INFORMATION**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

#### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c		5000	50000

### Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement, horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink hombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

# Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

# Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

# **SECTION 16: OTHER INFORMATION**

#### Legislation related to safety data sheets:

Date of compilation: 10/06/2019 Revised: 10/06/2019 Version: 2 (Replaced 1) Page 11/12

# Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

# PAVILAND TOP PU COLOR MATE (COMP. B)



# SECTION 16: OTHER INFORMATION (continued)

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

#### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

#### Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction H335: May cause respiratory irritation H336: May cause drowsiness or dizziness H226: Flammable liquid and vapour

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Acute Tox. 4: H332 - Harmful if inhaled

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation)

STOT SE 3: H335 - May cause respiratory irritation STOT SE 3: H336 - May cause drowsiness or dizziness

#### **Classification procedure:**

Skin Sens. 1: Calculation method STOT SE 3: Calculation method STOT SE 3: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

#### Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association

ICAO: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET 
Date of compilation: 10/06/2019 Revised: 10/06/2019 Version: 2 (Replaced 1) Page 12/12