



DECLARATION OF PERFORMANCES

Nº: 210085

1.- Product: MORCEMDRY R BLANCO

2.-Intended use: Mortar for rendering and plastering, CR CSIV W2, for the execution of waterproof coatings.

3.-Manufacturer: GRUPO PUMA ESPAÑA located in: Avda. Agrupación Córdoba 17,14014 Córdoba
www.grupopuma.com

4.-Evaluation system: 4

5.-Declared performances

Essential characteristics	Performance	Harmonized standards
Reaction to fire	A1 Type	EN-998-1:2018
Water absorption	W2	
Diffusion coefficient of water vapor	$\mu \leq 35$	
-Thermal conductivity :($\lambda_{10,Dry}$)	PND	
Adhesion	$\geq 0.3 \text{ N/mm}^2$ Breakage shape A/B	
Durability	NPD	
Hazardous substances	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3, in accordance with Regulation (EU) 2024/3110.

Signed by and on manufacturer's behalf:

Place and date of issue: Córdoba, 1/01/25

Technical Director: Jose A. Ferre Martínez



GRUPO PUMA ESPAÑA
Avda. Agrupación Córdoba 17, 14014 Córdoba
24
Nº: 210085

EN 998-1

MORCEMDRY R BLANCO

Colored mortar for rendering and plastering, CR, for the execution of waterproof coatings, up to 5 mm.

Reaction to fire:	A1 Type
Water absorption:	W2
Diffusion coefficient of water vapor:	$\mu \leq 35$
Adhesion:	$\geq 0.3 \text{ N/mm}^2$. Breakage shape A/B