

DECLARATION OF PERFORMANCES Nº: 210085

1. **Product:**
MORCEMDRY R BLANCO (CR CSIV W2)
2. **Manufacturer:**
GRUPO PUMA SL address:
C/ Conrado del Campo nº 2
29590 Campanillas (Málaga)
www.grupopuma.com
3. **Intended use:**
Rendering and plastering mortar, CR CSIV W2 for waterproof and coating execution.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performances	Harmonised Standards
Fire reaction	Class A1	IN-998-1:2010
Water absorption	W2	
Coefficient of water steam diffusion	$M \leq 25$	
Thermal Conductivity ($\lambda_{10,dry}$)	PND	
Adhesion	$> 0.3 \text{ N/mm}^2$ Breakage way A/B	
Durability	PND	
Dangerous Substances	See safety data sheet	

Product performances identified in point 1 are in accordance to performances stated in point 5
 This performance statement is issued under sole manufacturer responsibility indicated in point 3
 Signed by and on manufacturer behalf:
 Place and date of issue: Malaga, 1/07/2015



Technical Director: Jose A. Ferre Martínez

CE	
GRUPO PUMA SL C/ Conrado del Campo nº - 29590 Campanillas (Málaga). 14 Nº: 210085	
EN-998-1 MORCEMDRY R BLANCO Mortar for colored plastering and rendering, CR, for waterproof and coating execution, up to 5 mm	
Fire reaction:	Class A1
Water absorption:	W2
Coefficient of water steam diffusion:	$\mu \leq 25$
Adhesion:	$> 0.3 \text{ N/mm}^2$ Breakage way A/B

DECLARATION OF PERFORMANCES Nº: 210092

1. **Product:**
MORCEMDRY R GRIS (CR CSIV W2)
2. **Manufacturer:**
GRUPO PUMA SL address:
C/ Conrado del Campo nº 2
29590 Campanillas (Málaga)
www.grupopuma.com
3. **Intended use:**
Rendering and plastering mortar, CR CSIV W2 for waterproof and coating execution.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performances	Harmonised technical specification
Fire reaction	Class A1	IN-998-1:2010
Water absorption	W2	
Coefficient of water steam diffusion	$M \leq 25$	
Thermal Conductivity ($\lambda_{10,dry}$)	PND	
Adhesion	$> 0.3 \text{ N/mm}^2$ Breakage way A/B	
Durability	PND	
Dangerous Substances	See safety data sheet	

Product performances identified in point 1 are in accordance to performances stated in point 5
 This performance statement is issued under sole manufacturer responsibility indicated in point 3
 Signed by and on manufacturer behalf:
 Place and date of issue: Malaga, 1/07/2015



Technical Director: Jose A. Ferre Martínez

CE	
GRUPO PUMA SL C/ Conrado del Campo nº - 29590 Campanillas (Málaga). 14 Nº: 210085	
EN-998-1 MORCEMDRY R GRIS Mortar for colored plastering and rendering, CR, for waterproof and coating execution, up to 5 mm	
Fire reaction:	Class A1
Water absorption:	W2
Coefficient of water steam diffusion:	$\mu \leq 25$
Adhesion:	$> 0.3 \text{ N/mm}^2$ Breakage way A/B