

DECLARATION OF PERFORMANCES

Nº: 801153

1.- Product: MORCEMSEC PROYECTABLE EXTERIOR

2.-Intended use: Dry coating and cladding mortar of general purpose GP for outdoor and indoor plastering. Sprayable. For finishing layers up to 1,5 cm. Impermeable to rainwater.

3.-Manufacturer: GRUPO PUMA SL with registered address at: Avda. Agrupación Córdoba 17,14014 Córdoba www.grupopuma.com

4.-Evaluation System: 4

5.-Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class A1	EN-998-1:2010
Water absorption	W2	
Diffusion coefficient of water vapour	$\mu \leq 15$	
Thermal conductivity :($\lambda_{10,dry}$)	NPD	
Adhesion	$\geq 0.3 \text{ N/mm}^2$ Breakage method A/B	
Durability	NPD	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5.

This declaration of features is issued under the sole responsibility of manufacturer stated in point 3

Signed by and on manufacturer behalf:

Place and date of issue: Málaga, 28/05/2019



Technical Director: Jose A. Ferre Martínez



GRUPO PUMA SL
Avda Agrupación Córdoba 17
14014 Córdoba
05
Nº: 801153

EN 998-1

MORCEMSEC PROYECTABLE EXTERIOR

Dry coating and cladding mortar of general purpose GP for outdoor and indoor plastering. Sprayable. For finishing layers up to 1,5 cm. Impermeable to rainwater.

- Reaction to fire:** Class A1
- Water absorption:** W2
- Diffusion coefficient of water vapour:** $\mu \leq 15$
- Adhesion:** $\geq 0.3 \text{ N/mm}^2$ Breakage method A/B