



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PUMALASTIC PU (Blanco / Gris / Negro)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant.

1.3. Details of the supplier of the safety data sheet

GRUPO PUMA ESPAÑA SL
AVDA. AGRUPACIÓN CÓRDOBA, NUM. 17
14014 CÓRDOBA - CÓRDOBA - ESPAÑA
Tel.: +34 957 102 210 ° - Fax: +34 957 44 19 92
fds@grupopuma.com
<http://www.grupopuma.com>

1.4. Emergency telephone number

+34 957 102 210 (Horario de atención: 08:30 – 13:30 y de 16:00 – 19:00)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

A similar mixture has been tested for eye damage/irritation and the test results do not meet the criteria for classification.

The carcinogenicity classification for titanium dioxide is not applicable based on physical form (material is not a powder).

CLASSIFICATION:

Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334

For full text of H phrases, see Section 16.

2.2. Label elements



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
4,4'-methylenediphenyl diisocyanate	101-68-8	202-966-0	0.1 - < 1
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		915-687-0	< 0.1

HAZARD STATEMENTS:

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Information required per Regulation (EU) 2020/1149 as regards diisocyanates:

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures



SAFETY DATA SHEET
PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Poly(Vinyl Chloride)	(CAS-No.) 9002-86-2 (EC-No.) 618-338-8	20 - 50	Substance with a national occupational exposure limit
Reaction mass of ethylbenzene and xylene	(EC-No.) 905-588-0 (REACH-No.) 01-2119488216-32	3 - 7	Acute Tox. 4, H332 Acute Tox. 4, H312 Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373
Triiron tetraoxide	(CAS-No.) 1317-61-9 (EC-No.) 215-277-5 (REACH-No.) 01-2119457646-28	< 5	Substance not classified as hazardous
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 926-141-6 (REACH-No.) 01-2119456620-43	1 - 5	Asp. Tox. 1, H304 EUH066
Iron(III) oxide	(CAS-No.) 1309-37-1 (EC-No.) 215-168-2 (REACH-No.) 01-2119457614-35	< 5	Substance with a national occupational exposure limit
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-No.) 01-2119489379-17	< 5	Carc. 2, H351 (inhalation)
Calcium oxide	(CAS-No.) 1305-78-8 (EC-No.) 215-138-9 (REACH-No.) 01-2119475325-36	< 2.5	EUH071 Skin Corr. 1C, H314 Eye Dam. 1, H318
C.I. Pigment Yellow 42	(CAS-No.) 51274-00-1 (EC-No.) 257-098-5 (REACH-No.) 01-2119457554-33	< 2	Substance not classified as hazardous
4,4'-methylenediphenyl diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-	0.1 - < 1	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

	0 (REACH-No.) 01-2119457014-47		Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Nota 2,C
Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9 (REACH-No.) 01-2119384822-32	< 0.5	Substance with a national occupational exposure limit
Chromium oxide (Cr2O3)	(CAS-No.) 1308-38-9 (EC-No.) 215-160-9 (REACH-No.) 01-2119433951-39	< 0.5	Substance with a Union workplace exposure limit
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(EC-No.) 915-687-0 (REACH-No.) 01-2119491304-40	< 0.1	Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1 Skin Sens. 1A, H317

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
Calcium oxide	(CAS-No.) 1305-78-8 (EC-No.) 215-138-9 (REACH-No.) 01-2119475325-36	(C >= 50%) EUH071 (C >= 50%) Skin Corr. 1C, H314 (10% =< C < 50%) Skin Irrit. 2, H315 (C >= 3%) Eye Dam. 1, H318 (1% =< C < 3%) Eye Irrit. 2, H319 (20% =< C < 50%) STOT SE 3, H335
4,4'-methylenediphenyl diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-0 (REACH-No.) 01-2119457014-47	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 (C >= 0.1%) Resp. Sens. 1, H334 (C >= 5%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:
Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Isocyanates	During combustion.
Carbon monoxide	During combustion.
Hydrogen cyanide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Free isocyanates	101-68-8	UK HSC	TWA(as NCO):0.02 mg/m ³ ;STEL(as NCO):0.07 mg/m ³	Respiratory Sensitizer
Calcium oxide	1305-78-8	UK HSC	TWA(respirable fraction):1 mg/m ³ ;TWA:2 mg/m ³ ;STEL(respirable fraction):4 mg/m ³	
Chromium (III) oxide	1308-38-9	UK HSC	TWA(as Cr):0.5 mg/m ³	
Iron(III) oxide	1309-37-1	UK HSC	TWA(respirable):4 mg/m ³ ;TWA(Inhalable):10 mg/m ³ ;TWA(as Fe, fume):5 mg/m ³ ;STEL(as Fe, fume):10 mg/m ³	
Carbon black	1333-86-4	UK HSC	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³	
Titanium dioxide	13463-67-7	UK HSC	TWA(respirable):4 mg/m ³ ;TWA(Inhalable):10 mg/m ³	
Poly(Vinyl Chloride)	9002-86-2	UK HSC	TWA(as respirable dust):4 mg/m ³ ;TWA(as inhalable dust):10 mg/m ³	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
Free isocyanates	101-68-8	UK EH40 BMGVs	Isocyanate-derived diamine	Creatinine in urine	EPE	1 umol/mol	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EPE: At the end of the period of exposure.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	>0.30	> 8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Multicolor
Odor	Light Odor
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	137 °C
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	0.6 % volume
Flammable Limits(UEL)	8 % volume
Flash point	≥ 70 °C [<i>Test Method:ISO Method</i>] [<i>Details:3679</i>]
Autoignition temperature	≥ 200 °C
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture reacts with water</i>
Kinematic Viscosity	<i>No data available.</i>
Water solubility	Insoluble
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	<i>No data available.</i>
Relative density	1.16
Relative Vapor Density	<i>No data available.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Not determined

10.5 Incompatible materials

Alcohols.

Amines.

Alkali and alkaline earth metals.

Strong acids.

Water

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Prolonged or repeated exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Poly(Vinyl Chloride)	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly(Vinyl Chloride)	Ingestion		LD50 estimated to be > 5,000 mg/kg
Reaction mass of ethylbenzene and xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Reaction mass of ethylbenzene and xylene	Inhalation-Vapour (4 hours)	Rat	LC50 29 mg/l
Reaction mass of ethylbenzene and xylene	Ingestion	Rat	LD50 3,523 mg/kg
Iron(III) oxide	Dermal	Not available	LD50 3,100 mg/kg
Iron(III) oxide	Ingestion	Not available	LD50 3,700 mg/kg
Triiron tetraoxide	Dermal	Not available	LD50 3,100 mg/kg
Triiron tetraoxide	Ingestion	Not available	LD50 3,700 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Calcium oxide	Ingestion	Rat	LD50 > 2,500 mg/kg
Calcium oxide	Dermal	similar compounds	LD50 > 2,500 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation-Vapour	Professional judgement	LC50 estimated to be 20 - 50 mg/l



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
Chromium oxide (Cr2O3)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Chromium oxide (Cr2O3)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.41 mg/l
Chromium oxide (Cr2O3)	Ingestion	Rat	LD50 > 5,000 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Rat	LD50 3,125 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Poly(Vinyl Chloride)	Professional judgement	No significant irritation
Reaction mass of ethylbenzene and xylene	Rabbit	Mild irritant
Iron(III) oxide	Rabbit	No significant irritation
Triiron tetraoxide	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Calcium oxide	Human	Corrosive
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Minimal irritation
4,4'-methylenediphenyl diisocyanate	official classification	Irritant
Carbon black	Rabbit	No significant irritation
Chromium oxide (Cr2O3)	Rabbit	No significant irritation
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
Reaction mass of ethylbenzene and xylene	Rabbit	Mild irritant
Iron(III) oxide	Rabbit	No significant irritation
Triiron tetraoxide	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Calcium oxide	Rabbit	Corrosive
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
4,4'-methylenediphenyl diisocyanate	official classification	Severe irritant
Carbon black	Rabbit	No significant irritation
Chromium oxide (Cr2O3)	Rabbit	No significant irritation
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rabbit	No significant irritation



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Skin Sensitisation

Name	Species	Value
Iron(III) oxide	Human	Not classified
Triiron tetraoxide	Human	Not classified
Titanium dioxide	Human and animal	Not classified
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Guinea pig	Not classified
4,4'-methylenediphenyl diisocyanate	official classification	Sensitising
Chromium oxide (Cr2O3)	similar compounds	Not classified
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Guinea pig	Sensitising

Respiratory Sensitisation

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Poly(Vinyl Chloride)	In Vitro	Not mutagenic
Reaction mass of ethylbenzene and xylene	In Vitro	Not mutagenic
Reaction mass of ethylbenzene and xylene	In vivo	Not mutagenic
Iron(III) oxide	In Vitro	Not mutagenic
Triiron tetraoxide	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Calcium oxide	In Vitro	Not mutagenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic
4,4'-methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification
Chromium oxide (Cr2O3)	In vivo	Not mutagenic
Chromium oxide (Cr2O3)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Poly(Vinyl Chloride)	Not specified.	Rat	Some positive data exist, but the data are not sufficient for classification
Reaction mass of ethylbenzene and xylene	Dermal	Rat	Not carcinogenic
Reaction mass of ethylbenzene and xylene	Ingestion	Multiple animal species	Not carcinogenic
Reaction mass of ethylbenzene and xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Iron(III) oxide	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Triiron tetraoxide	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal	Not carcinogenic



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

		species	
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not available	Not carcinogenic
4,4'-methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.
Chromium oxide (Cr2O3)	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Poly(Vinyl Chloride)	Not specified.	Not classified for development	Mouse	NOAEL Not available	during gestation
Reaction mass of ethylbenzene and xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Reaction mass of ethylbenzene and xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
Reaction mass of ethylbenzene and xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	1 generation
4,4'-methylenediphenyl diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Chromium oxide (Cr2O3)	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	90 days
Chromium oxide (Cr2O3)	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	90 days
Chromium oxide (Cr2O3)	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	90 days

Lactation

Name	Route	Species	Value
Reaction mass of ethylbenzene and xylene	Ingestion	Mouse	Not classified for effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Reaction mass of ethylbenzene and xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Reaction mass of ethylbenzene and xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Reaction mass of ethylbenzene and xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Reaction mass of ethylbenzene and xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Reaction mass of ethylbenzene and xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Reaction mass of ethylbenzene and xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Reaction mass of ethylbenzene and xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
Calcium oxide	Inhalation	respiratory irritation	May cause respiratory irritation	Not available	NOAEL Not available	occupational exposure
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Chromium oxide (Cr2O3)	Inhalation	respiratory system	Not classified	Rat	NOAEL 40 mg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Poly(Vinyl Chloride)	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.013 mg/l	22 months
Reaction mass of ethylbenzene and xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Reaction mass of ethylbenzene and xylene	Inhalation	auditory system	May cause damage to organs through prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Reaction mass of ethylbenzene and xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Reaction mass of ethylbenzene and xylene	Inhalation	heart endocrine system gastrointestinal tract hematopoietic system muscles kidney and/or bladder respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Reaction mass of ethylbenzene and xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Reaction mass of ethylbenzene and xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Reaction mass of ethylbenzene and xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
Reaction mass of ethylbenzene and xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Iron(III) oxide	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Triiron tetraoxide	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Chromium oxide (Cr2O3)	Inhalation	immune system respiratory system	Not classified	Rat	NOAEL 44 mg/m3	90 days



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

		hematopoietic system liver kidney and/or bladder				
--	--	--	--	--	--	--

Aspiration Hazard

Name	Value
Reaction mass of ethylbenzene and xylene	Aspiration hazard
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Poly(Vinyl Chloride)	9002-86-2		Data not available or insufficient for classification			N/A
Reaction mass of ethylbenzene and xylene	905-588-0	Green Algae	Estimated	73 hours	EC50	1.3 mg/l
Reaction mass of ethylbenzene and xylene	905-588-0	Rainbow trout	Estimated	96 hours	LC50	2.6 mg/l
Reaction mass of ethylbenzene and xylene	905-588-0	Water flea	Estimated	24 hours	IC50	1 mg/l
Reaction mass of ethylbenzene and xylene	905-588-0	Green Algae	Estimated	73 hours	NOEC	0.44 mg/l
Reaction mass of ethylbenzene and xylene	905-588-0	Rainbow trout	Estimated	56 days	NOEC	>1.3 mg/l
Reaction mass of ethylbenzene and xylene	905-588-0	Water flea	Estimated	7 days	NOEC	0.96 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes,	926-141-6	Water flea	Experimental	48 hours	EL50	>1,000 mg/l



SAFETY DATA SHEET
PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

cyclics, <2% aromatics						
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	NOEL	1,000 mg/l
Iron(III) oxide	1309-37-1	Golden Orfe	Experimental	48 hours	LC50	>1,000 mg/l
Triiron tetraoxide	1317-61-9	Bacteria	Experimental	6 hours	EC50	>50,000 mg/l
Triiron tetraoxide	1317-61-9	Green Algae	Experimental	72 hours	EC50	>50,000 mg/l
Triiron tetraoxide	1317-61-9	Water flea	Experimental	48 hours	EC50	>50,000 mg/l
Triiron tetraoxide	1317-61-9	Green Algae	Experimental	72 hours	EC0	>50,000 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Calcium oxide	1305-78-8	Common Carp	Experimental	96 hours	LC50	1,070 mg/l
C.I. Pigment Yellow 42	51274-00-1	Bacteria	Experimental	16 hours	NOEC	1,000 mg/l
C.I. Pigment Yellow 42	51274-00-1	Water flea	Experimental	48 hours	EC50	100 mg/l
C.I. Pigment Yellow 42	51274-00-1	Zebra Fish	Experimental	96 hours	LC50	>100,000 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Green algae	Estimated	72 hours	EC50	>1,640 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Water flea	Estimated	24 hours	EC50	>1,000 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Zebra Fish	Estimated	96 hours	LC50	>1,000 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Green algae	Estimated	72 hours	NOEC	1,640 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Water flea	Estimated	21 days	NOEC	10 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	EC50	>=100 mg/l
Carbon black	1333-86-4		Data not available or insufficient for classification			N/A
Chromium oxide (Cr2O3)	1308-38-9	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
Chromium oxide (Cr2O3)	1308-38-9	Water flea	Estimated	48 hours	No tox obs at lmt of water sol	>100 mg/l
Chromium oxide (Cr2O3)	1308-38-9	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Chromium oxide (Cr2O3)	1308-38-9	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l



SAFETY DATA SHEET
PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Chromium oxide (Cr2O3)	1308-38-9	Water flea	Estimated	21 days	No tox obs at lmt of water sol	>100 mg/l
Chromium oxide (Cr2O3)	1308-38-9	Zebra Fish	Estimated	30 days	No tox obs at lmt of water sol	>100 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Activated sludge	Experimental	3 hours	IC50	>=100 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Green algae	Experimental	72 hours	EC50	1.68 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Zebra Fish	Experimental	96 hours	LC50	0.9 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Green algae	Experimental	72 hours	NOEC	0.22 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Water flea	Experimental	21 days	NOEC	1 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Poly(Vinyl Chloride)	9002-86-2	Data not availbl-insufficient			N/A	
Reaction mass of ethylbenzene and xylene	905-588-0	Experimental Biodegradation	28 days	BOD	98 % BOD/ThBOD	OECD 301F - Manometric respirometry
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Experimental Biodegradation	28 days	BOD	69 % BOD/ThBOD	OECD 301F - Manometric respirometry
Iron(III) oxide	1309-37-1	Data not availbl-insufficient			N/A	
Triiron tetraoxide	1317-61-9	Data not availbl-insufficient			N/A	
Titanium dioxide	13463-67-7	Data not availbl-insufficient			N/A	
Calcium oxide	1305-78-8	Data not availbl-insufficient			N/A	
C.I. Pigment	51274-00-1	Data not availbl-			N/A	



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Yellow 42		insufficient				
4,4'-methylenediphenyl diisocyanate	101-68-8	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	Non-standard method
Carbon black	1333-86-4	Data not available - insufficient			N/A	
Chromium oxide (Cr2O3)	1308-38-9	Data not available - insufficient			N/A	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Estimated Biodegradation	28 days	Dissolv. Organic Carbon Deplet	38 % weight	OECD 301E - Modif. OECD Screen

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Poly(Vinyl Chloride)	9002-86-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Reaction mass of ethylbenzene and xylene	905-588-0	Experimental BCF - Rainbow Trout	56 days	Bioaccumulation factor	25.9	Non-standard method
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Iron(III) oxide	1309-37-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Triiron tetraoxide	1317-61-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF- Carp	42 days	Bioaccumulation factor	9.6	Non-standard method
Calcium oxide	1305-78-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
C.I. Pigment Yellow 42	51274-00-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
4,4'-methylenediphenyl diisocyanate	101-68-8	Experimental BCF- Carp	28 days	Bioaccumulation factor	200	OECD 305E - Bioaccumulation flow-through fish test
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Chromium oxide (Cr2O3)	1308-38-9	Estimated BCF - Other		Bioaccumulation factor	800	Non-standard method
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Estimated BCF- Carp	56 days	Bioaccumulation factor	31.4	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
4,4'-	101-68-8	Estimated Mobility	Koc	34,000 l/kg	Episuite™



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

methylenediphenyl diisocyanate		in Soil			
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Estimated Mobility in Soil	Koc	200,000 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

Not regulated for transportation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Iron(III) oxide	1309-37-1	Gr. 3: Not classifiable	International Agency for Research on Cancer
4,4'-methylenediphenyl diisocyanate	101-68-8	Carc. 2	Regulation (EC) No.



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

4,4'-methylenediphenyl diisocyanate	101-68-8	Gr. 3: Not classifiable	1272/2008, Table 3.1 International Agency for Research on Cancer
Poly(Vinyl Chloride)	9002-86-2	Gr. 3: Not classifiable	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
4,4'-methylenediphenyl diisocyanate	101-68-8

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H351i	Suspected of causing cancer by inhalation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Revision information:

EU Section 09: pH information information was added.

Section 02: CLP Restriction 74 Statement information was added.



SAFETY DATA SHEET

PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Label: CLP Percent Unknown information was deleted.
Label: CLP Supplemental Hazard Statements information was added.
Section 03: Composition table % Column heading information was added.
Section 3: Composition/ Information of ingredients table information was modified.
Section 03: SCL table information was added.
Section 03: Substance not applicable information was added.
Section 04: First Aid - Symptoms and Effects (CLP) information was added.
Section 04: Information on toxicological effects information was modified.
Section 6: Accidental release clean-up information information was modified.
Section 8: glove data value information was modified.
Section 8: Occupational exposure limit table information was modified.
Section 8: Personal Protection - Skin/hand information information was modified.
Section 9: Evaporation Rate information information was deleted.
Section 9: Explosive properties information information was deleted.
Section 9: Flash point information information was modified.
Section 09: Kinematic Viscosity information information was added.
Section 9: Melting point information information was modified.
Section 9: Oxidising properties information information was deleted.
Section 9: pH information information was deleted.
Section 9: Property description for optional properties information was modified.
Section 9: Vapour density value information was added.
Section 9: Vapour density value information was deleted.
Section 9: Viscosity information information was deleted.
Section 11: Acute Toxicity table information was modified.
Section 11: Classification disclaimer information was modified.
Section 11: No endocrine disruptor information available warning information was added.
Section 12: 12.6. Endocrine Disrupting Properties information was added.
Section 12: 12.7. Other adverse effects information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Contact manufacturer for more detail. information was deleted.
Section 12: Mobility in soil information information was added.
Section 12: No endocrine disruptor information available warning information was added.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Section 14 Classification Code – Main Heading information was added.
Section 14 Classification Code – Regulation Data information was added.
Section 14 Control Temperature – Main Heading information was added.
Section 14 Control Temperature – Regulation Data information was added.
Section 14 Disclaimer Information information was added.
Section 14 Emergency Temperature – Main Heading information was added.
Section 14 Emergency Temperature – Regulation Data information was added.
Section 14 Hazard Class + Sub Risk – Main Heading information was added.
Section 14 Hazard Class + Sub Risk – Regulation Data information was added.
Section 14 Hazardous/Not Hazardous for Transportation information was added.
Section 14 Multiplier – Main Heading information was added.
Section 14 Multiplier – Regulation Data information was added.
Section 14 Other Dangerous Goods – Main Heading information was added.
Section 14 Other Dangerous Goods – Regulation Data information was added.
Section 14 Packing Group – Main Heading information was added.
Section 14 Packing Group – Regulation Data information was added.
Section 14 Proper Shipping Name information was added.
Section 14 Regulations – Main Headings information was added.
Section 14 Segregation – Regulation Data information was added.
Section 14 Segregation Code – Main Heading information was added.
Section 14 Special Precautions – Main Heading information was added.
Section 14 Special Precautions – Regulation Data information was added.



SAFETY DATA SHEET
PUMALASTIC PU (Blanco / Gris / Negro)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Section 14 Transport Category – Main Heading information was added.
Section 14 Transport Category – Regulation Data information was added.
Section 14 Transport in bulk – Regulation Data information was added.
Section 14 Transport in bulk according to Annex II of Marpol and the IBC Code – Main Heading information was added.
Section 14 Transport Not Permitted – Main Heading information was added.
Section 14 Transport Not Permitted – Regulation Data information was added.
Section 14 Tunnel Code – Main Heading information was added.
Section 14 Tunnel Code – Regulation Data information was added.
Section 14 UN Number Column data information was added.
Section 14 UN Number information was added.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

PUMALASTIC PU (Beige/Terracota)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Sealant.

1.3. Details of the supplier of the safety data sheet

GRUPO PUMA ESPAÑA SL
AVDA. AGRUPACIÓN CÓRDOBA, NUM. 17
14014 CÓRDOBA - CÓRDOBA - ESPAÑA
Tfno.: +34 957 102 210 - Fax: +34 957 44 19 92
fds@grupopuma.com
<http://www.grupopuma.com>

1.4. Emergency telephone number 957 102 210 (Horario de atención: 08:30 – 13:30 y de 16:00 – 19:00)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

A similar mixture has been tested for eye damage/irritation and the test results do not meet the criteria for classification.

The carcinogenicity classification for titanium dioxide is not applicable based on physical form (material is not a powder).

CLASSIFICATION:

Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334

For full text of H phrases, see Section 16.

2.2. Label elements



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
4,4'-methylenediphenyl diisocyanate	101-68-8	202-966-0	0.1 - < 1
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		915-687-0	< 0.1

HAZARD STATEMENTS:

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

Information required per Regulation (EU) 2020/1149 as regards diisocyanates:

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures



SAFETY DATA SHEET
PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Poly(Vinyl Chloride)	(CAS-No.) 9002-86-2 (EC-No.) 618-338-8	20 - 50	Substance with a national occupational exposure limit
Reaction mass of ethylbenzene and xylene	(EC-No.) 905-588-0 (REACH-No.) 01-2119488216-32	3 - 7	Acute Tox. 4, H332 Acute Tox. 4, H312 Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 926-141-6 (REACH-No.) 01-2119456620-43	1 - 5	Asp. Tox. 1, H304 EUH066
Iron(III) oxide	(CAS-No.) 1309-37-1 (EC-No.) 215-168-2 (REACH-No.) 01-2119457614-35	< 5	Substance with a national occupational exposure limit
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5 (REACH-No.) 01-2119489379-17	< 5	Carc. 2, H351 (inhalation)
Calcium oxide	(CAS-No.) 1305-78-8 (EC-No.) 215-138-9 (REACH-No.) 01-2119475325-36	< 2.5	EUH071 Skin Corr. 1C, H314 Eye Dam. 1, H318
Triiron tetraoxide	(CAS-No.) 1317-61-9 (EC-No.) 215-277-5 (REACH-No.) 01-2119457646-28	< 2	Substance not classified as hazardous
4,4'-methylenediphenyl diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-0 (REACH-No.) 01-2119457014-47	0.1 - < 1	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Nota 2,C

Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9 (REACH-No.) 01-2119384822-32	< 0.5	Substance with a national occupational exposure limit
Chromium oxide (Cr2O3)	(CAS-No.) 1308-38-9 (EC-No.) 215-160-9 (REACH-No.) 01-2119433951-39	< 0.5	Substance with a Union workplace exposure limit
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(EC-No.) 915-687-0 (REACH-No.) 01-2119491304-40	< 0.1	Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1 Skin Sens. 1A, H317

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
Calcium oxide	(CAS-No.) 1305-78-8 (EC-No.) 215-138-9 (REACH-No.) 01-2119475325-36	(C >= 50%) EUH071 (C >= 50%) Skin Corr. 1C, H314 (10% =< C < 50%) Skin Irrit. 2, H315 (C >= 3%) Eye Dam. 1, H318 (1% =< C < 3%) Eye Irrit. 2, H319 (20% =< C < 50%) STOT SE 3, H335
4,4'-methylenediphenyl diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-0 (REACH-No.) 01-2119457014-47	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 (C >= 0.1%) Resp. Sens. 1, H334 (C >= 5%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:
Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Isocyanates	During combustion.
Carbon monoxide	During combustion.
Hydrogen cyanide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Free isocyanates	101-68-8	UK HSC	TWA(as NCO):0.02 mg/m ³ ;STEL(as NCO):0.07 mg/m ³	Respiratory Sensitizer
Calcium oxide	1305-78-8	UK HSC	TWA(respirable fraction):1 mg/m ³ ;TWA:2 mg/m ³ ;STEL(respirable fraction):4 mg/m ³	
Chromium (III) oxide	1308-38-9	UK HSC	TWA(as Cr):0.5 mg/m ³	
Iron(III) oxide	1309-37-1	UK HSC	TWA(respirable):4 mg/m ³ ;TWA(Inhalable):10 mg/m ³ ;TWA(as Fe, fume):5 mg/m ³ ;STEL(as Fe, fume):10 mg/m ³	
Carbon black	1333-86-4	UK HSC	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³	
Titanium dioxide	13463-67-7	UK HSC	TWA(respirable):4 mg/m ³ ;TWA(Inhalable):10 mg/m ³	
Poly(Vinyl Chloride)	9002-86-2	UK HSC	TWA(as respirable dust):4 mg/m ³ ;TWA(as inhalable dust):10 mg/m ³	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
------------	---------	--------	-------------	---------------------	---------------	-------	---------------------



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Free isocyanates 101-68- UK EH40 Isocyanate- Creatinine in EPE 1 umol/mol
8 BMGVs derived urine
diamine

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)
EPE: At the end of the period of exposure.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.5	> 8 hours
Fluoroelastomer	0.4	> 8 hours
Neoprene.	0.5	> 8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Multicolor
Odor	Light Odor
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	137 °C
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	0.6 % volume
Flammable Limits(UEL)	8 % volume
Flash point	≥ 70 °C [<i>Test Method:ISO Method</i>] [<i>Details:3679</i>]
Autoignition temperature	≥ 200 °C
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture reacts with water</i>
Kinematic Viscosity	<i>No data available.</i>
Water solubility	Insoluble
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	<i>No data available.</i>
Relative density	1.16
Relative Vapor Density	<i>No data available.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>

SECTION 10: Stability and reactivity



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Not determined

10.5 Incompatible materials

Alcohols.

Amines.

Strong acids.

Alkali and alkaline earth metals.

Water

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Prolonged or repeated exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Poly(Vinyl Chloride)	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly(Vinyl Chloride)	Ingestion		LD50 estimated to be > 5,000 mg/kg
Reaction mass of ethylbenzene and xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Reaction mass of ethylbenzene and xylene	Inhalation-Vapour (4 hours)	Rat	LC50 29 mg/l
Reaction mass of ethylbenzene and xylene	Ingestion	Rat	LD50 3,523 mg/kg
Iron(III) oxide	Dermal	Not available	LD50 3,100 mg/kg
Iron(III) oxide	Ingestion	Not available	LD50 3,700 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Calcium oxide	Ingestion	Rat	LD50 > 2,500 mg/kg
Calcium oxide	Dermal	similar compounds	LD50 > 2,500 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Inhalation-Vapour	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Triiron tetraoxide	Dermal	Not available	LD50 3,100 mg/kg
Triiron tetraoxide	Ingestion	Not available	LD50 3,700 mg/kg
4,4'-methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

4,4'-methylenediphenyl diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg
Chromium oxide (Cr2O3)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Chromium oxide (Cr2O3)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.41 mg/l
Chromium oxide (Cr2O3)	Ingestion	Rat	LD50 > 5,000 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Ingestion	Rat	LD50 3,125 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Poly(Vinyl Chloride)	Professional judgement	No significant irritation
Reaction mass of ethylbenzene and xylene	Rabbit	Mild irritant
Iron(III) oxide	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Calcium oxide	Human	Corrosive
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Minimal irritation
Triiron tetraoxide	Rabbit	No significant irritation
4,4'-methylenediphenyl diisocyanate	official classification	Irritant
Carbon black	Rabbit	No significant irritation
Chromium oxide (Cr2O3)	Rabbit	No significant irritation
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
Reaction mass of ethylbenzene and xylene	Rabbit	Mild irritant
Iron(III) oxide	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Calcium oxide	Rabbit	Corrosive
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
Triiron tetraoxide	Rabbit	No significant irritation
4,4'-methylenediphenyl diisocyanate	official classification	Severe irritant
Carbon black	Rabbit	No significant irritation
Chromium oxide (Cr2O3)	Rabbit	No significant irritation
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Iron(III) oxide	Human	Not classified



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Titanium dioxide	Human and animal	Not classified
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Guinea pig	Not classified
Triiron tetraoxide	Human	Not classified
4,4'-methylenediphenyl diisocyanate	official classification	Sensitising
Chromium oxide (Cr2O3)	similar compounds	Not classified
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Guinea pig	Sensitising

Respiratory Sensitisation

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Poly(Vinyl Chloride)	In Vitro	Not mutagenic
Reaction mass of ethylbenzene and xylene	In Vitro	Not mutagenic
Reaction mass of ethylbenzene and xylene	In vivo	Not mutagenic
Iron(III) oxide	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Calcium oxide	In Vitro	Not mutagenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic
Triiron tetraoxide	In Vitro	Not mutagenic
4,4'-methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification
Chromium oxide (Cr2O3)	In vivo	Not mutagenic
Chromium oxide (Cr2O3)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Poly(Vinyl Chloride)	Not specified.	Rat	Some positive data exist, but the data are not sufficient for classification
Reaction mass of ethylbenzene and xylene	Dermal	Rat	Not carcinogenic
Reaction mass of ethylbenzene and xylene	Ingestion	Multiple animal species	Not carcinogenic
Reaction mass of ethylbenzene and xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Iron(III) oxide	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not available	Not carcinogenic
Triiron tetraoxide	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

4,4'-methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.
Chromium oxide (Cr2O3)	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Poly(Vinyl Chloride)	Not specified.	Not classified for development	Mouse	NOAEL Not available	during gestation
Reaction mass of ethylbenzene and xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Reaction mass of ethylbenzene and xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
Reaction mass of ethylbenzene and xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	1 generation
4,4'-methylenediphenyl diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0,004 mg/l	during organogenesis
Chromium oxide (Cr2O3)	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	90 days
Chromium oxide (Cr2O3)	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	90 days
Chromium oxide (Cr2O3)	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	90 days

Lactation

Name	Route	Species	Value
Reaction mass of ethylbenzene and xylene	Ingestion	Mouse	Not classified for effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Reaction mass of ethylbenzene and xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Reaction mass of ethylbenzene and xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Reaction mass of ethylbenzene and xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Reaction mass of ethylbenzene and xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Reaction mass of ethylbenzene and xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Reaction mass of ethylbenzene and xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Reaction mass of	Ingestion	eyes	Not classified	Rat	NOAEL 250	not applicable



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

ethylbenzene and xylene					mg/kg	
Calcium oxide	Inhalation	respiratory irritation	May cause respiratory irritation	Not available	NOAEL Not available	occupational exposure
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Chromium oxide (Cr2O3)	Inhalation	respiratory system	Not classified	Rat	NOAEL 40 mg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Poly(Vinyl Chloride)	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.013 mg/l	22 months
Reaction mass of ethylbenzene and xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Reaction mass of ethylbenzene and xylene	Inhalation	auditory system	May cause damage to organs through prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Reaction mass of ethylbenzene and xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Reaction mass of ethylbenzene and xylene	Inhalation	heart endocrine system gastrointestinal tract hematopoietic system muscles kidney and/or bladder respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Reaction mass of ethylbenzene and xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Reaction mass of ethylbenzene and xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Reaction mass of ethylbenzene and xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
Reaction mass of ethylbenzene and xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Iron(III) oxide	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Triiron tetraoxide	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Chromium oxide (Cr2O3)	Inhalation	immune system respiratory system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 44 mg/m3	90 days



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Aspiration Hazard

Name	Value
Reaction mass of ethylbenzene and xylene	Aspiration hazard
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Poly(Vinyl Chloride)	9002-86-2		Data not available or insufficient for classification			N/A
Reaction mass of ethylbenzene and xylene	905-588-0	Green Algae	Estimated	73 hours	EC50	1.3 mg/l
Reaction mass of ethylbenzene and xylene	905-588-0	Rainbow trout	Estimated	96 hours	LC50	2.6 mg/l
Reaction mass of ethylbenzene and xylene	905-588-0	Water flea	Estimated	24 hours	IC50	1 mg/l
Reaction mass of ethylbenzene and xylene	905-588-0	Green Algae	Estimated	73 hours	NOEC	0.44 mg/l
Reaction mass of ethylbenzene and xylene	905-588-0	Rainbow trout	Estimated	56 days	NOEC	>1.3 mg/l
Reaction mass of ethylbenzene and xylene	905-588-0	Water flea	Estimated	7 days	NOEC	0.96 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Green Algae	Experimental	72 hours	NOEL	1,000 mg/l



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

alkanes, isoalkanes, cyclics, <2% aromatics						
Iron(III) oxide	1309-37-1	Golden Orfe	Experimental	48 hours	LC50	>1,000 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Calcium oxide	1305-78-8	Common Carp	Experimental	96 hours	LC50	1,070 mg/l
Triiron tetraoxide	1317-61-9	Bacteria	Experimental	6 hours	EC50	>50,000 mg/l
Triiron tetraoxide	1317-61-9	Green Algae	Experimental	72 hours	EC50	>50,000 mg/l
Triiron tetraoxide	1317-61-9	Water flea	Experimental	48 hours	EC50	>50,000 mg/l
Triiron tetraoxide	1317-61-9	Green Algae	Experimental	72 hours	EC0	>50,000 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Green algae	Estimated	72 hours	EC50	>1,640 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Water flea	Estimated	24 hours	EC50	>1,000 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Zebra Fish	Estimated	96 hours	LC50	>1,000 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Green algae	Estimated	72 hours	NOEC	1,640 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Water flea	Estimated	21 days	NOEC	10 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	EC50	>=100 mg/l
Carbon black	1333-86-4		Data not available or insufficient for classification			N/A
Chromium oxide (Cr2O3)	1308-38-9	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
Chromium oxide (Cr2O3)	1308-38-9	Water flea	Estimated	48 hours	No tox obs at lmt of water sol	>100 mg/l
Chromium oxide (Cr2O3)	1308-38-9	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Chromium oxide (Cr2O3)	1308-38-9	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
Chromium oxide (Cr2O3)	1308-38-9	Water flea	Estimated	21 days	No tox obs at lmt of water sol	>100 mg/l
Chromium oxide (Cr2O3)	1308-38-9	Zebra Fish	Estimated	30 days	No tox obs at lmt of water sol	>100 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Activated sludge	Experimental	3 hours	IC50	>=100 mg/l



SAFETY DATA SHEET
PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Green algae	Experimental	72 hours	EC50	1.68 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Zebra Fish	Experimental	96 hours	LC50	0.9 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Green algae	Experimental	72 hours	NOEC	0.22 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Water flea	Experimental	21 days	NOEC	1 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Poly(Vinyl Chloride)	9002-86-2	Data not availbl-insufficient			N/A	
Reaction mass of ethylbenzene and xylene	905-588-0	Experimental Biodegradation	28 days	BOD	98 % BOD/ThBOD	OECD 301F - Manometric respirometry
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Experimental Biodegradation	28 days	BOD	69 % BOD/ThBOD	OECD 301F - Manometric respirometry
Iron(III) oxide	1309-37-1	Data not availbl-insufficient			N/A	
Titanium dioxide	13463-67-7	Data not availbl-insufficient			N/A	
Calcium oxide	1305-78-8	Data not availbl-insufficient			N/A	
Triiron tetraoxide	1317-61-9	Data not availbl-insufficient			N/A	
4,4'-methylenediphenyl diisocyanate	101-68-8	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	Non-standard method
Carbon black	1333-86-4	Data not availbl-insufficient			N/A	
Chromium oxide (Cr2O3)	1308-38-9	Data not availbl-insufficient			N/A	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-	915-687-0	Estimated Biodegradation	28 days	Dissolv. Organic Carbon Deplet	38 % weight	OECD 301E - Modif. OECD Screen



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

pentamethyl-4-piperidyl sebacate					
----------------------------------	--	--	--	--	--

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Poly(Vinyl Chloride)	9002-86-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Reaction mass of ethylbenzene and xylene	905-588-0	Experimental BCF - Rainbow Trout	56 days	Bioaccumulation factor	25.9	Non-standard method
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	926-141-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Iron(III) oxide	1309-37-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation factor	9.6	Non-standard method
Calcium oxide	1305-78-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Triiron tetraoxide	1317-61-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
4,4'-methylenediphenyl diisocyanate	101-68-8	Experimental BCF-Carp	28 days	Bioaccumulation factor	200	OECD 305E - Bioaccumulation flow-through fish test
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Chromium oxide (Cr2O3)	1308-38-9	Estimated BCF - Other		Bioaccumulation factor	800	Non-standard method
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Estimated BCF-Carp	56 days	Bioaccumulation factor	31.4	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
4,4'-methylenediphenyl diisocyanate	101-68-8	Estimated Mobility in Soil	Koc	34,000 l/kg	Episuite™
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	Estimated Mobility in Soil	Koc	200,000 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

Not regulated for transportation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Iron(III) oxide	1309-37-1	Gr. 3: Not classifiable	International Agency for Research on Cancer
4,4'-methylenediphenyl diisocyanate	101-68-8	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
4,4'-methylenediphenyl diisocyanate	101-68-8	Gr. 3: Not classifiable	International Agency for Research on Cancer
Poly(Vinyl Chloride)	9002-86-2	Gr. 3: Not classifiable	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
4,4'-methylenediphenyl diisocyanate	101-68-8



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H351i	Suspected of causing cancer by inhalation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Revision information:

EU Section 09: pH information information was added.

Section 02: CLP Restriction 74 Statement information was added.

Label: CLP Percent Unknown information was deleted.

Label: CLP Supplemental Hazard Statements information was added.

Section 03: Composition table % Column heading information was added.

Section 3: Composition/ Information of ingredients table information was modified.

Section 03: SCL table information was added.

Section 03: Substance not applicable information was added.

Section 04: First Aid - Symptoms and Effects (CLP) information was added.

Section 04: Information on toxicological effects information was modified.

Section 6: Accidental release clean-up information information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 9: Evaporation Rate information information was deleted.

Section 9: Explosive properties information information was deleted.

Section 9: Flash point information information was modified.

Section 09: Kinematic Viscosity information information was added.

Section 9: Melting point information information was modified.



SAFETY DATA SHEET

PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

Section 9: Oxidising properties information information was deleted.
Section 9: pH information information was deleted.
Section 9: Property description for optional properties information was modified.
Section 9: Vapour density value information was added.
Section 9: Vapour density value information was deleted.
Section 9: Viscosity information information was deleted.
Section 11: Acute Toxicity table information was modified.
Section 11: Classification disclaimer information was modified.
Section 11: Health Effects - Ingestion information information was modified.
Section 11: No endocrine disruptor information available warning information was added.
Section 12: 12.6. Endocrine Disrupting Properties information was added.
Section 12: 12.7. Other adverse effects information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Contact manufacturer for more detail. information was deleted.
Section 12: Mobility in soil information information was added.
Section 12: No endocrine disruptor information available warning information was added.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Section 14 Classification Code – Main Heading information was added.
Section 14 Classification Code – Regulation Data information was added.
Section 14 Control Temperature – Main Heading information was added.
Section 14 Control Temperature – Regulation Data information was added.
Section 14 Disclaimer Information information was added.
Section 14 Emergency Temperature – Main Heading information was added.
Section 14 Emergency Temperature – Regulation Data information was added.
Section 14 Hazard Class + Sub Risk – Main Heading information was added.
Section 14 Hazard Class + Sub Risk – Regulation Data information was added.
Section 14 Hazardous/Not Hazardous for Transportation information was added.
Section 14 Multiplier – Main Heading information was added.
Section 14 Multiplier – Regulation Data information was added.
Section 14 Other Dangerous Goods – Main Heading information was added.
Section 14 Other Dangerous Goods – Regulation Data information was added.
Section 14 Packing Group – Main Heading information was added.
Section 14 Packing Group – Regulation Data information was added.
Section 14 Proper Shipping Name information was added.
Section 14 Regulations – Main Headings information was added.
Section 14 Segregation – Regulation Data information was added.
Section 14 Segregation Code – Main Heading information was added.
Section 14 Special Precautions – Main Heading information was added.
Section 14 Special Precautions – Regulation Data information was added.
Section 14 Transport Category – Main Heading information was added.
Section 14 Transport Category – Regulation Data information was added.
Section 14 Transport in bulk – Regulation Data information was added.
Section 14 Transport in bulk according to Annex II of Marpol and the IBC Code – Main Heading information was added.
Section 14 Transport Not Permitted – Main Heading information was added.
Section 14 Transport Not Permitted – Regulation Data information was added.
Section 14 Tunnel Code – Main Heading information was added.
Section 14 Tunnel Code – Regulation Data information was added.
Section 14 UN Number Column data information was added.
Section 14 UN Number information was added.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the



SAFETY DATA SHEET
PUMALASTIC PU (Beige / Terracota)

Revision date: 01/04/2024
Version: 4 (Replaced 3)

product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.