

## DECLARATION OF PERFORMANCES

### Nº: 100050-434

- 1. Product:**  
PEGOLAND GEL PORCELANICO C2TE BLANCO
- 2. Manufacturer:**  
GRUPO PUMA SL with registered address at:  
Avda. Agrupación Córdoba, 17  
14014 Córdoba (Córdoba)  
www.grupopuma.com
- 3. Intended use:**  
Improved cementitious adhesive with reduced slip and extended open time, Pegoland Gel Porcelanico C2TE Blanco. For the installation of interior and exterior flooring, interior wall and baseboards, swimming pool linings and, radiant heating and overlaps in interior flooring, adhesion of all types of ceramic tiles, porcelain stoneware, marble, granite and natural stone.
- 4. Evaluation system:**  
3
- 5. Notified bodies:**  
They have performed the type tests No. 01-18/032172/1 dated October 2018, 01-19/043045/1 dated November 2019, 01-21/001079/1 dated January 2021 and 01-21/006896/1, 01-21/005758/1, 01-21/006034/1 01-21/006865/1 and 1-21/006032/1 dated March 2021, at CEMOSA No. 1377 (Malaga) obtaining the same product results for all factories.
- 6. Declared performances:**

Essential characteristics	Performances	Harmonised technical specification
<b>Reaction to fire</b>	Class E	EN-12004:2008+A1:2012
<b>Adhesion:</b> - Initial tensile adhesion strength:	$\geq 1\text{N/mm}^2$	
<b>Durability:</b> - Tensile adhesion after water immersion: - Tensile adhesion after heat aging: - Tensile adhesion after freeze/thaw cycles:	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
<b>Dangerous substances:</b>	See Safety Datasheet	

The performances of the product identified in point 1 comply with the performances declared in point 6.  
This declaration of features is issued under the sole responsibility of the manufacturer stated in point 2  
Signed for on behalf of the manufacturer by:  
Date and place of issue: Malaga, 30/03/2021



Technical Director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 19	
<b>PEGOLAND GEL PORCELANICO C2TE BLANCO</b>  <b>Nº: 100050-434</b>  <b>EN-12004:2008+A1:2012</b>  Improved cementitious adhesive with reduced slip and extended open time, for floors and walls, interior and exterior application.	
<b>Reaction to fire:</b>	Class E
<b>Adhesion:</b>	
- Initial tensile adhesion:	$\geq 1\text{N/mm}^2$
<b>Durabilidad:</b>	
- Tensile adhesion after water immersion:	$\geq 1\text{N/mm}^2$
- Tensile adhesion after heat aging:	$\geq 1\text{N/mm}^2$
- Tensile adhesion after freeze/thaw cycles:	$\geq 1\text{N/mm}^2$
<b>Dangerous substances:</b>	See safety Datasheet