

DECLARATION OF PERFORMANCES

Nº: 120018-157

1. **Product:**
PEGOLAND PLUS GRIS

2. **Manufacturer:**
GRUPO PUMA SL with address at:
C)) Conrado del Campo nº
29590 Campanillas (Málaga)
www.grupopuma.com

3. **Intended use:**
Normal setting cementitious adhesive with reduced slip, Pegoland Plus Gris, for gluing in interiors, exterior floors and baseboards with absorption of > 3 %.

4. **Evaluation system:**
3

5. **Notified bodies:**
They have carried out the type tests nº 71383, 71410, 71436, 71448, 73591, 75254, 75454, 75469, 80106 dated February, March, April, May, June 2004 , nº 2703403 dated March 2007 and 0201-01-2013-7062 dated October 2013 at CEMOSA nº 1377 (Málaga) and nº 4019120 dated November 2004, nº 5029471 dated July 2005, nº 31212761 dated August 2006 in APPLUS nº 0370 (Barcelona) obtaining the same product results for all factories.

6. **Declared performances:**

Essential characteristics	Performances	Harmonized technical specifications
Reaction to fire:	Class E	EN-12004:2007+A1:2012
Adherence: - Initial tensile adhesion	≥ 0,5N/mm ²	
Durability: - Tensile adhesion after immersion in water - Tensile adhesion after thermal aging - Tensile adhesion after freeze/thaw cycles	≥ 0,5N/mm ² ≥ 0,5N/mm ² ≥ 0,5N/mm ²	
Hazardous substances:	See Safety Data Sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6
This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.
Signed by and on behalf of the manufacturer:

Place and Date of issue: Málaga, 01/07/2015



Technical director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA SL C) Conrado del Campo nº 2 29590 Campanillas (Málaga) 04	
PEGOLAND PLUS GRIS Nº: 120018-157 EN 12004: 2007 + A1:2012 Cementitious adhesive of normal setting with reduced slip, for floors and walls. for floors and walls, for interior and exterior application.	
Reaction to fire:	Class E
Adherence:	
- Initial tensile adhesion:	$\geq 0,5\text{N/mm}^2$
Durability:	
- Tensile adhesion after immersion in water	$\geq 0,5\text{N/mm}^2$
- Tensile adhesion after thermal aging	$\geq 0,5\text{N/mm}^2$
- Tensile adhesion after freeze/thaw cycles	$\geq 0,5\text{N/mm}^2$
Hazardous substances:	See safety data sheet