

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUMACRIL REVESTIMIENTO SILICATO

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

PUMACRIL REVESTIMIENTO SILICATO

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Paint

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

GRUPO PUMA ESPAÑA S.L. AVDA. AGRUPACIÓN CÓRDOBA, NUM. 17 14014 CÓRDOBA - CÓRDOBA - ESPAÑA Phone: +34 957 102 210 - Fax: +34 957 44 19 92 fds@grupopuma.com http://www.grupopuma.com

1.4 Emergency telephone number: +34 957 102 210 (Horario de atención: 08:30 – 13:30 y de 16:00 – 19:00)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

The product is not classified as hazardous according to CLP Regulation (EC) No 1272/2008.

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Hazard statements:

Non-applicable

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

Supplementary information:

P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

EUH210: Safety data sheet available on request.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aqueous mixture composed of additives, aggregates, coalescents, pigments and resins

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification		Chemical name/Classification				
CAS: 64742-82-1	naphtha (petroleum)	, hydrodesulphurized heavy , < 0.1 % EC 200-753-7 1	ATP ATP05			
EC: 265-185-4 Index: 649-330-00-2 REACH: 01-2119490979-12- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	(1) (1) (1) (1)	1 - <2,5 %		
¹ Substances presenting a	ealth or environmental hazar	d which meet criteria laid down in Regulation (EU) No. 2020/878				

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.



SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUMACRIL REVESTIMIENTO SILICATO

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

- A.- Technical measures for storage
 - Minimum Temp.: 5 °C
 - Maximum Temp.: 35 °C
- B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short exposure		Long e	xposure
Identification		Systemic	Local	Systemic	Local
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-82-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 265-185-4	Inhalation	1286,4 mg/m ³	1066,67 mg/m ³	Non-applicable	837,5 mg/m ³

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-82-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 265-185-4	Inhalation	1152 mg/m ³	640 mg/m ³	Non-applicable	178,57 mg/m ³

PNEC:

Non-applicable

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

[Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E Ī	Body protection				
	Distagram	DDE	Loballing	CEN Standard	Domostka

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulation: in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CAT II	EN ISO 20347:2012	Replace before any evidence of deterioration. Fo periods of prolonged exposure to the product fo professional/industrial users CE III is recommended, in accordance with the regulation in EN ISO 20345:2012 y EN 13832-1:2007



Emergency measure	Standards	Emergency measure	Standards
^ +	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	◎ + ▼	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:20
Emergency shower		Eyewash stations	
Environmental exposure cont	trols:		
	ty legislation for the protection of its container. For additional inform		
With regard to Directive 2010/75	/EU, this product has the following	g characteristics:	
V.O.C. (Supply):	1,01 % weight		
V.O.C. density at 20 °C:	14,08 kg/m ³ (14,08 g/L)		
Average carbon number:	8,96		
Average molecular weight:	119,64 g/mol		
	/EC, this product which is ready to	use has the following ch	aracteristics:
V.O.C. density at 20 °C:	14,08 kg/m ³ (14,08 g/L)	5	
EU limit for the product (Cat.			
Components:	Non-applicable		
ION 9: PHYSICAL AND CHEM	IICAL PROPERTIES		
Information on basic physica	l and chemical properties:		
For complete information see the			
For complete information see the Appearance:	product datasheet.		
For complete information see the Appearance: Physical state at 20 °C:	product datasheet. Liquid		
For complete information see the Appearance: Physical state at 20 °C: Appearance:	product datasheet. Liquid Paste	hle	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour:	product datasheet. Liquid Paste Not availal		
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour:	product datasheet. Liquid Paste Not availal Not availal	ble	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold:	product datasheet. Liquid Paste Not availal	ble	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility:	e product datasheet. Liquid Paste Not availal Not availal Not availal Non-applic	ble	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric pres	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C	ble	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric pressons Vapour pressure at 20 °C:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa	ble sable *	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61	ble cable * Pa (12,32 kPa)	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa	ble cable * Pa (12,32 kPa)	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour : Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Product description:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61 Non-applic	ble cable * Pa (12,32 kPa) cable *	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61 Non-applic 1400 kg/m	ble cable * Pa (12,32 kPa) cable *	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61 Non-applic 1400 kg/m 1,4	ble cable * Pa (12,32 kPa) cable *	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61 1 Non-applic 1400 kg/m 1,4 Non-applic	ble cable * Pa (12,32 kPa) cable *	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61 Non-applic 1400 kg/m 1,4	ble cable * Pa (12,32 kPa) cable *	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61 I Non-applic 1400 kg/m 1,4 Non-applic Non-applic Non-applic Non-applic	ple cable * Pa (12,32 kPa) cable * n ³ cable * cable * cable *	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61 Non-applic 1400 kg/m 1,4 Non-applic Non-applic	ple cable * Pa (12,32 kPa) cable * n ³ cable * cable * cable *	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61 I Non-applic 1400 kg/m 1,4 Non-applic Non-applic Non-applic Non-applic	ple cable * Pa (12,32 kPa) cable * n ³ cable * cable * cable *	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61 Non-applic 1400 kg/m 1,4 Non-applic Non-applic >20,5 mm Non-applic	pole cable * Pa (12,32 kPa) cable * rable * cable * cable * cable *	
For complete information see the Appearance: Physical state at 20 °C: Appearance: Colour: Odour the Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH:	e product datasheet. Liquid Paste Not availal Not availal Non-applic sure: 101 °C 2339 Pa 12324,61 I Non-applic 1400 kg/m 1,4 Non-applic Non-applic 20,5 mm Non-applic 10 - 12 Non-applic	ple cable * Pa (12,32 kPa) cable * n ³ cable * cable * cable * cable *	

Revised: 11/08/2023



SECT	TON 9: PHYSICAL AND CHEMICAL PROPERTIES	S (continued)
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	Non Flammable (>60 °C)
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	275 °C
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
9.2	Other information:	
	Information with regard to physical hazard clas	ses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *
	Other safety characteristics:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	Safety data sheet valid for colors	
	*Not relevant due to the nature of the product, not providing info	rmation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity	
	Not applicable	Not applicable	Precaution	Precaution	Not applicable	
	0.5 Incompatible materials:					
10.5	Incompatible materials	:				
10.5	Incompatible materials Acids	Water	Oxidising materials	Combustible materials	Others	

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO), carbon monoxide and other organic compounds

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3

Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.

Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.

Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: propan-2-ol (3); Talc (3); naphtha (petroleum), hydrodesulphurized heavy, < 0.1 % EC 200-753-7 (3)

Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acut	e toxicity	Genus
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	LD50 oral	5100 mg/kg	Rat
CAS: 64742-82-1	LD50 dermal	3160 mg/kg	Rabbit
EC: 265-185-4	LC50 inhalation	12 mg/L (6 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	LC50	Non-applicable		
CAS: 64742-82-1	EC50	4,3 mg/L (96 h)	Crangon crangon	Crustacean
EC: 265-185-4	EC50	Non-applicable		

12.2 Persistence and degradability:

Not available

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccur	nulation potential
naphtha (petroleum), hydrodesulphurized heavy , < 0.1 % EC 200-753-7	BCF	645
CAS: 64742-82-1	Pow Log	4
EC: 265-185-4	Potential	High

12.4 Mobility in soil:

Not available

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

	Code	Description	Waste class (Regulation (EU) No 1357/2014)
	08 01 12	waste paint and varnish other than those mentioned in 08 01 11	Non-hazardous

Type of waste (Regulation (EU) No 1357/2014):

Non-applicable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUMACRIL REVESTIMIENTO SILICATO

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Non-applicable

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

Version: 3 (Replaced 2)

Revised: 11/08/2023