

## DECLARATION OF PERFORMANCES

Nº: 230042

**1.- Product:**

MORCEMDRY SF PLUS

**2.- Intended use:**

Waterproofing product for concrete, applied in liquid phase.

**3.- Manufacturer:**

GRUPO PUMA SL with registered address: Avda Agrupación Córdoba nº 17 ,14014 Córdoba www.grupopuma.com

**4.-System of evaluation and verification of the constancy of performance of products (EVCP) :**

3 for water tightness and 4 for other characteristics.

**5.- Notified body:**

Applus nº 0370

**6.- Declared performances:**

Essential characteristics	Performances	Notes	Harmonised technical specifications
Initial tensile bond strength	$\geq 0.5 \text{ N/mm}^2$	A.6.2	UNE- EN-14891:2017
Watertight	Sem penetração	A.7	
Resistance to crack propagation	$\geq 0.75 \text{ mm}$	A.8 and declared conditions	
Initial tensile adhesion durability with weathering/temperal ageing	$0.5 \text{ N/mm}^2$	A.6.5	
Initial tensile adhesion durability with water/humidity action	$\geq 0.5 \text{ N/mm}^2$	A.6.3 ó A.6.4	
Initial tensile adhesion durability with contact with lime water	$\geq 0.5 \text{ N/mm}^2$	A.6.9	
Initial grip durability in traction with frost and freeze/thaw cycles	$\geq 0.5 \text{ N/mm}^2$	A.6.6	
Hazardous Substances	Paragraph 4.2		

The performance of the product identified in point 1 is in conformity with the performance declared in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 3, in accordance with Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer:

Place and date of issue: Cordoba 08/08/2018.



Technical director: Jose A. Ferre Martínez



0370

GRUPO PUMA SL

Avda. Agrupación Córdoba nº 17 ,14014 Córdoba  
18

Nº: 230042

**UNE-EN-14891**

**MORCEMDRY SF PLUS**

Cementitious waterproofing product applied in liquid phase for all outdoor applications and swimming pools under ceramic tiles.

<b>Initial tensile bond strength</b>	<b>≥ 0.5 N/mm<sup>2</sup></b>
<b>Watertight</b>	<b>No penetration</b>
<b>Resistance to crack propagation</b>	<b>≥ 0.75 mm</b>
<b>Initial tensile adhesion durability with weathering/ temperal ageing</b>	<b>≥ 0.5 N/mm<sup>2</sup></b>
<b>Initial tensile adhesion durability with water/humidity action</b>	<b>≥ 0.5 N/mm<sup>2</sup></b>
<b>Initial tensile adhesion durability with contact with lime water</b>	<b>≥ 0.5 N/mm<sup>2</sup></b>
<b>Initial grip durability in traction with frost and freeze/thaw cycles</b>	<b>≥ 0.5 N/mm<sup>2</sup></b>