

DECLARATION OF PERFORMANCES

Nº: 120100-137

1.- Product: PEGOLAND PORCELÁNICO BLANCO

2.- Manufacturer: GRUPO PUMA SL with registered address at: C) Conrado del Campo nº 2 29590 Campanillas (Malaga). www.grupopuma.com

3.- Intended use: Cement based normal setting tile adhesive with reduced slip and extended open time, Pegoland Max Plus Gris, for bonding ceramic tiles with water absorption < 3 % for internal walls and internal and external floorings.

4.- Evaluation system: 3

5.- Notified bodies: The following initial type tests have been conducted: 71346, 71384, 71405, 71434, 71487, 74049, 75253, 75394, 75451, 75465, 75471, 75475, dated February, March, April 2004, and nº 2508369 dated August 2005, in CEMOSA nº 1377 (Málaga), and nº 23010056 , 4019119 dated February and September 2004, nº 08-5019 dated October 2008, in APPLUS nº 0370 (Barcelona) with the same results obtained in all factories.

6.- Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Class E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength:	$\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion: - Tensile adhesion after heat aging: - Tensile adhesion after freeze/thaw cycles:	$\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$	
Dangerous substances:	See Safety Datasheet	

The performances of the product identified in point 1 comply with the performances declared in point 6.

This declaration of features is issued under the sole responsibility of the manufacturer stated in point 2

Signed for on behalf of the manufacturer by:

Date and place of issue: Malaga, 1/07/2015



Technical Director: Jose A. Ferre Martínez



0370, 1377

GRUPO PUMA SL

C) Conrado del Campo nº 2 29590 Campanillas (Málaga).
04

PEGOLAND PORCELANICO BLANCO

Nº: 120100-137

EN 12004: 2007+A1:2012

Cement based tile adhesive with reduce slip and extended open time for internal walls and internal and external floorings.

Reaction to fire:

Class E

Adhesion:

- Initial tensile adhesion

$\geq 0.5 \text{ N/mm}^2$

Durability:

- Tensile adhesion after water immersion:

$\geq 0.5 \text{ N/mm}^2$

- Tensile adhesion after heat aging:

$\geq 0.5 \text{ N/mm}^2$

- Tensile adhesion after freeze/thaw cycles:

$\geq 0.5 \text{ N/mm}^2$

Dangerous substances

See Safety Datasheet

DECLARATION OF PERFORMANCES

Nº: 120117-130

1.- Product: PEGOLAND PORCELÁNICO GRIS

2.- Manufacturer: GRUPO PUMA SL with registered address at: C) Conrado del Campo nº 2 29590 Campanillas (Malaga). www.grupopuma.com

3.- Intended use: Cement based normal setting tile adhesive with reduced slip and extended open time, Pegoland Max Plus Gris, for bonding ceramic tiles with water absorption < 3 % for internal walls and internal and external floorings.

4.- Evaluation system: 3

5.- Notified bodies: The following initial type tests , have been conducted: 71347,71386, 71406, 71417,71431, 71437, 71486, 75397, 75449, 75465 ,80107 dated February, March, April and June 2004, in CEMOSA nº 1377 (Málaga), and nº 4021730 dated September 2004 and nº 5029470, 5026638 dated July and September 2005, nº 31212763 dated August 2006, in APPLUS nº 0370 (Barcelona) with the same results obtained in all factories.

6.- Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Class E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength:	$\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion: - Tensile adhesion after heat aging: - Tensile adhesion after freeze/thaw cycles:	$\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$	
Dangerous substances:	See Safety Datasheet	

The performances of the product identified in point 1 comply with the performances declared in point 6. This declaration of features is issued under the sole responsibility of the manufacturer stated in point 2
Signed for on behalf of the manufacturer by:
Date and place of issue: Malaga, 1/07/2015



Technical Director: Jose A. Ferre Martínez



0370, 1377

GRUPO PUMA SL

C) Conrado del Campo nº 2 29590 Campanillas (Málaga).
04

PEGOLAND PORCELANICO GRIS

Nº: 120117-130

EN 12004: 2007+A1:2012

Cement based normal setting tile adhesive with reduce slip and extended open time for internal walls and internal and external floorings.

Reaction to fire:

Class E

Adhesion:

- Initial tensile adhesion

$\geq 0.5 \text{ N/mm}^2$

Durability:

- Tensile adhesion after water immersion:

$\geq 0.5 \text{ N/mm}^2$

- Tensile adhesion after heat aging:

$\geq 0.5 \text{ N/mm}^2$

- Tensile adhesion after freeze/thaw cycles:

$\geq 0.5 \text{ N/mm}^2$

Dangerous substances

See Safety Datasheet