

DECLARATION OF PERFORMANCE

No.: 110064


1. **Product:**
PEGOLAND GRIS
2. **Manufacturer:**
GRUPO PUMA ESPAÑA located at:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Pegoland Grey cementitious adhesive for the installation of interior floor and wall tiles. Suitable for bonding ceramic tiles with medium to high water absorption. Not suitable for exterior applications.
4. **Evaluation system:**
3
5. **Notified bodies:**
Type tests No. 71351, 71358, 71363, 71377, 71388, 71394, 71411, 71439, 71444, 71454, 71457, 71468, 71470, 71472, 71483, 74809, 81169 and 87258 were carried out in February, March, April, June and September 2004 at CEMOSA No. 1377 (Málaga), and Test No. 31212766 was carried out in August 2006 at APPLUS No. 0370 (Barcelona), obtaining the same product performance results for all manufacturing plants.
6. **Declared performances:**

Essential characteristics	Performances	Harmonized Technical Specification
Reaction to fire:	A1fl and A1 Class	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after thermal ageing - Tensile adhesion strength after freeze-thaw cycles	$\geq 0.5\text{N/mm}^2$ NPD NPD	
Hazardous substances:	See safety data sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on behalf of the manufacturer:

Place and date of issue: Málaga, 02/01/2025



Technical Director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 04	
PEGOLAND GRIS Nº: 110064 EN-12004:2007+A1:2012 Cementitious adhesive for floors and walls, not suitable for exterior applications.	
Reaction to fire:	A1fl and A1 Class
Adhesion: - Initial tensile adhesion strength:	≥ 0.5N/mm ²
Durability: - Tensile adhesion strength after water immersion	≥ 0.5N/mm ²
Hazardous substances:	See safety data sheet