

DECLARACION OF PERFORMANCES Nº: 860020

1. **Product:**
MORCEMCAL PIEDRA
2. **Manufacturer:**
GRUPO PUMA SL with registered address:
Avda. AGRUPACIÓN CÓRDOBA, Núm.17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Rendering and plastering mortar for common use G, based on natural hydraulic lime, for taping and repair of walls and masonry and natural stone factories.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performances	Harmonized standards
Proportion of components	Cement: 0% Lime: 46% Aggregates: 54%	EN-998-2:2012
Adhesion	NPD	
Chloride content	NPD	
Reaction to fire	Class A1	
Water absorption	NPD	
Water vapor permeability	$\leq \mu 6$	
Thermal conductivity (λ_{10}, dry)	NPD	
Durability	NPD	
Hazardous substances	See safety data sheet	

The performance of the product identified in item 1 is in conformity with the performance declared in item 5
This declaration of performance is issued under the sole responsibility of the manufacturer indicated in item 2
Signed by and on behalf of the manufacturer:
Place and Date of issue: Córdoba, 24/07/2020



Technical director: Jose A. Ferre Martínez



GRUPO PUMA SL
 Avda. Agrupación Córdoba, Núm.17
 14014 CÓRDOBA
 11

MORCEMCAL PIEDRA

Nº: 860020

EN 998-2

Rendering and plastering mortar for common use G, based on natural hydraulic lime, for taping and repair of walls and masonry and natural stone factories.

Proportion of components

Cement: 0%
 Lime: 46%
 Aggregates: 54%

Reaction to fire:

Class A1

Water vapour permeability

$\mu \leq 6$