



DECLARATION OF PERFORMANCES
Nº: 821370

1.- Product

MORCEM ESTUCO LISO

2.- Manufacturer

GRUPO PUMA ESPAÑA, S.L.

located in

Avda. AGRUPACION CORDOBA, Nº 17

14014 CORDOBA

www.grupopuma.com

3.- Intended use

Coating mortar based on aerial lime for plastering with a fine finishes, floated or smooth finish. Impervious to rainwater and permeable to water vapour.

4.- Evaluation system

4

5.- Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type A1	EN 998-1:2018
Water absorption	W2	
Diffusion coefficient of water vapour	$\mu \leq 15$	
Thermal conductivity: ($\lambda_{10, dry}$)	0,76 W/mK (tabulated value)	
Adhesion	$\geq 0,2 \text{ N/mm}^2$ Failure mode B	
Durability	Assessment based on valid dispositions at the intended place of use of the mortar.	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2, in accordance with Regulation (EU) Nº 305/2011

Signed by and on manufacturer behalf:

Place and date of issue: Córdoba, 15/05/2024

Manager: Jose A. Ferre Martínez



	
GRUPO PUMA ESPAÑA, S.L. Avda. AGRUPACION CORDOBA, Nº 17 14014 CORDOBA	
21	
MORCEM ESTUCO LISO Nº: 821370 EN 998-1 Coating mortar based on aerial lime for plastering with a fine finishes, floated or smooth finish. Impervious to rainwater and permeable to water vapour.	
Reaction to fire	Type A1
Water absorption	W2
Diffusion coefficient of water vapour	$\mu \leq 15$
Adhesion	0,76 W/mK (tabulated value)
Thermal conductivity: ($\lambda_{10, dry}$)	$\geq 0,2 \text{ N/mm}^2$ Failure mode B
Durability	Evaluation based on valid provisions at the intended place of use of mortar
Hazardous substances	See safety datasheet