

DECLARATION OF PERFORMANCES

Nº: 230043

1.- Product: MORCEMDRY PU

2.-Intended use: Polymeric polyurethane coating for concrete surface protection and waterproofing of concrete.

3.-Manufacturer: GRUPO PUMA SL with registered address: C) Conrado del Campo nº 2 29590 Campanillas (Málaga).www.grupopuma.com

4.-Evaluation system: 4

5. Declared Performances:

Essential characteristics	Performances	Harmonised standards
Direct tensile adhesion	$\geq 2.0\text{Mpa}$	EN-1504-2: 2004
Rigid systems with traffic loads.		
Water vapor permeability	Class II	
Capillary absorption and liquid water permeability.	$\leq 0.1\text{Kgm}^{-2}\cdot\text{h}^{-0.5}$	
Hazardous substances	See Safety Data Sheet	
Reaction to fire	Class F	

The performance of the product identified in point 1 is in conformity with the performance declared in point 5.

This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 3.

Signed by and on behalf of the manufacturer:

Place and Date of issue: Málaga 7.08.17

Technical director: Jose A. Ferre Martínez





GRUPO PUMA SL
C) Conrado del Campo nº 2 29590 Campanillas
(Málaga). 12
Nº: 230043

EN 1504-2

MORCEMDRY E

**Polymeric epoxy coating for surface protection of concrete
and waterproofing of concrete.**

Direct tensile adhesion : ≥ 2.0 Mpa

Water vapor permeability: Class II

Capillary absorption: $\leq 0.1 \text{ Kg m}^{-2} \text{ h}^{-0.5}$

Reaction to fire: Class F