

DECLARATION OF PERFORMANCES Nº: 800033

1. **Product:**
MORCEMSEC CAPA FINA BLANCO
2. **Manufacturer:**
GRUPO PUMA S.L with registered address at:
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Colored plastering and rendering mortar, CR, for exterior and interior sprayed plastering, for finishing and finishing up to 1 cm, impermeable to rainwater.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class A1	EN-998-1:2018
Water absorption	W2	
Water vapor diffusion coefficient	$\mu \leq 15$	
Thermal conductivity: ($\lambda_{10, dry}$)	PND	
Adhesion	≥ 0.3 N/mm ² Breakage form A/B	
Durability	PND	
Hazardous substances	See Safety Data Sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.

Signed by and on behalf of the manufacturer:
Place and Date of issue: Cordoba, 16/03/21



Technical Director: Jose A. Ferre Martínez



GRUPO PUMA S.L
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
18

MORCEMSEC CAPA FINA

Nº: 800033

EN 998-1

Colored plastering and rendering mortar, CR, for exterior and interior sprayed plastering, for finishing and finishing up to 1 cm, impermeable to rainwater.

Reaction to fire	Class A1
Water absorption	W2
Water vapor diffusion coefficient	$\mu \leq 15$
Adhesion	≥ 0.3 N/mm ² Breakage form A/B