

DECLARATION OF PERFORMANCES

Nº: 105283

1. **Product:**
PEGOLAND FAST FLEX
2. **Manufacturer:**
GRUPO PUMA SL with address at:
Avda. Agrupación Córdoba nº17
14014 Córdoba.
www.grupopuma.com
3. **Intended use:**
Improved fast setting cementitious adhesive, with extended open time, reduced slip and highly deformable Pegoland Fast Flex for the placement of all types of ceramic tiles in floor and wall coverings, interior and exterior, especially suitable for placement on exterior facades.
4. **Evaluation system:**
3
5. **Notified bodies:**
They have made the type test No. 0201-01-2014-4479 dated June 23, 2014 in CEMOSA No. 1377 (Malaga).
6. **Declared performances:**


Essential characteristics	Performances	Harmonized technical specifications
Reaction to fire:	Class E	EN-12004:2007+A1:2012
Adherence: - Initial tensile adhesion	$\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after immersion in water - Tensile adhesion after thermal aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances:	See Safety Data Sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6
This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.
Signed by and on behalf of the manufacturer:

Place and Date of issue: Málaga, 07/08/2018



Technical director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA SL Avda. Agrupación Córdoba nº17 14014 Córdoba. 14	
PEGOLAND FAST FLEX Nº: 105283 EN 12004: 2007 + A1:2012 Improved fast setting cementitious adhesive , with extended open time, reduced sliding and highly deformable , for the placement of all types of ceramic tiles in floor and wall ceramic tiles in pavements and coverings, interior and exterior, especially suitable for the placement in exterior facades.	
Reaction to fire:	Class E
Adherence:	
- Initial tensile adhesion:	$\geq 1\text{N/mm}^2$
Durability:	
- Tensile adhesion after immersion in water	$\geq 1\text{N/mm}^2$
- Tensile adhesion after thermal aging	$\geq 1\text{N/mm}^2$
- Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$
Hazardous substances:	See safety data sheet