

Insulation mortars

WalAce EIFS system

Walace MORTAR

Walace Ancillary

Unofin ACRYLIC BASECOAT

Unofin ACRYLIC TEXTURE

Pidilite Puma



WalAce MORTAR

Mortar for the adhesion of expanded polystyrene (EPS) panels and mineral wool.

Characteristics

Hydraulic mortar used as an adhesive and covering on EPS or XPS or MW panels in the external insulation finishing system WalAce EIFS. This mortar, has great adhesion, waterproofing, easy application and does not spread the flame. It is permeable to water vapour.







± 8 kg/m²

25 kg bags

Grey

Uno Fin ACRYLIC BASECOAT

Color base for acrylic mortar.

Characteristics

High-quality acrylic base. Improves adhesion, facilitates application, evens out the absorption properties of the surface material, and provides an initial coat of color. Enhances the performance of the finishing acrylic mortar, maintaining a high permeability to water vapor. Excellent application, workability and adhesion to the surface.







± 4 at 5 m²/Kg

20 kg plastic buckets

Colour range

Unofin ACRYLIC TEXTURE

Synthetic mineral plaster.

Characteristics

For waterproofing and decorating all types of exterior and interiors walls and ceilings. Quick and easy application. Excellent adhesion to typical construction surfaces. Waterproof, washable, and resistant to mold and mildew. Resistant to aging. Coat thickness from 2 to 3 mm. Thin/ Medium/thick/Grated finishes.







± 4 at 5 m²/Kg

20 kg plastic buckets

Colour range

WalAce ANCILLARY

WalAce PANELS



WalAce

WalAce ANCHORING SCREWS/PLUGS



WalAcePROFILES





